Про Аудио ЕООД
гр. Бургас
ул. Гладстон № 83
тел/факс 056 / 845204
web: http://www.proaudio.bg
e-mail: contact@proaudio.bg



Професионално осветление

Ценова листа
2014

COMPACT HYBRID MOVING HEADS

ENTERTAINMENT

MAX

*IP20 (for Indoor installations)



Code	Description	Цена без ДДС	Цена с ДДС
03.MS014.EBLFP	**MAX FPR black** ***Lamp:** MSD PLATINUM 16R 330W (16.000 Lumens) ***Optical group:** Improved optical group made with 11 coated lenses, 100.000 Lux at 5 m, Motorized wide-excursion linear zoom ***Beam opening:** 1,5° - 2° (Beam projection), 2° - 37° (Spot projection), 10° - 60° (Wash projection), 4° - 40° (Studio projection), 16-bit motorized linear focus, Motorized Iris, Linear dimmer, Frost filter ***Colour generation:** Linear CMY, Linear CTO, Colour wheel (17 colours + white) with linear, selection for perfect 2-colour beams ***Dynamic effects:** Overlapping wheels for multiple effects: Customizable rotating gobo wheel (9 gobos), Customizable fixed gobo wheel (10 gobos), Animation Wheel, 4-facet rotating prism ***Interface / Control / Programming:** Li-Fe backup battery for controlling the main parameters even when MAX is not powered, RDM, ARTNET available on request, Wireless ready, Updatable internal operating system ***DMX:** 33 DMX channels ***Pan & Tilt:** 'FPR' system (D.T.S. patent), Pan (limitless, in both directions); Tilt (270°), Tri-phase stepper motor technology for ultra-fast silent Pan / Tilt movements, Pan 540°: 2,5 sec.; Tilt 270°: 1,5 sec., 16-bit resolution, Pan / Tilt lock ***Power supply:** Electronic ballast: 90-260 V 50 / 60 Hz ***Power Consumption:** 450 W with PFC ***Weight:** 20 Kg ***Safety:** Overvoltage circuit protection and overtemperature circuit protection ***International certifications:** Safety: EN 60598-1: 1993; EN 60598-2-17: 1989; A1-A3: 1993; EMC: EN 55015. ***Included items:** 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027) *Omega clamp (2 pieces) (cod. 02K00549) ***Packing:** (LxDxH) 610 x 510 x 515 mm *25 Kg	**9 575.00 лв.**	11 490.00 лв.
03.MS014.EB.L	**MAX black** *Same as MAX FPR but without FPR movement *Pan 540° (2,5 sec.); Tilt 270° (1,5 sec.)	**8 880.00 лв.**	10 656.00 лв.
RAL 9003	**.03 WHITE** option — *White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.
	.WS option — *Assembled with Wireless Board + 2 Dbi IP65 Antenna on board **(Extra Cost)***	***304.00 лв.***	364.80 лв.

JACK

*IP20 (for Indoor installations)



Code	Description	Цена без ДДС	Цена с ДДС
03.MS012.EBLFP	**JACK FPR black** ***Lamp:** MSD Platinum 5R (7.950 Lumens) ***Optical group:** Improved optical group made with 11 coated lenses, Motorized wide-excursion linear zoom ***Beam opening:** 1° - 2,5° (Beam projection), 2,5° - 37° (Spot projection), 38° - 46° (Wash projection), 16-bit motorized linear focus, Motorized iris, Linear dimmer ***Colour generation:** Colour wheel (17 colours + white) with linear selection for perfect 2-colour beams ***Dynamic effects:** Overlapping wheels for multiple effects:, Customizable rotating gobo wheel (9 gobos), Customizable fixed gobo wheel (10 gobos), 4-facet rotating prism ***Interface / Control / Programming:** RDM, ARTNET available on request, Wireless ready, Updatable internal operating system ***DMX:** 25 DMX channels ***Pan & Tilt:** 'FPR' system (D.T.S. patent): limitless Pan, rotation in both directions, Tri-phase stepper motor technology,for ultra-fast silent Pan / Tilt movements, Pan 540°: 2,5 sec.; Tilt 270°: 1,5 sec., 16-bit resolution ***Power supply:** Electronic ballast: 90-260 V 50 / 60 Hz ***Power Consumption:** 230 W with PFC, Power saving mode (the lamp dims to 80% after shutter closure) ***Weight:** 11,9 Kg ***Connectors:** DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON connectors (Power In / Power Out) by Neutrik ***Safety:** Overvoltage circuit protection and overtemperature circuit protection ***International certifications:** Safety: EN 60598-1: 1993; EN 60598-2-17: 1989; A1-A3: 1993; EMC: EN 55015 ***Included items:** 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027); "C" Clamp G QUICK with(one piece) (cod. 0521A014) ***Packing:** (LxDxH) 535 x 435 x 420 mm *15,50 Kg	**5 200.00 лв.**	6 240.00 лв.
03.MS012.EB.L	**JACK black** *Same as JACK FPR but without FPR movement *Pan 540° (2,5 sec.); Tilt 270° (1,5 sec.)	**4 825.00 лв.**	5 790.00 лв.
RAL 9003	**.03 WHITE** option — *White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.
	.WS option — *Assembled with Wireless Board + 2 Dbi IP65 Antenna on board **(Extra Cost)***	***304.00 лв.***	364.80 лв.

COMPACT BEAM MOVING HEADS

ENTERTAINMENT

RAPTOR

*IP20 (for Indoor installations)



Code	Description	Цена без ДДС	Цена с ДДС
03.MB005.EB.LFP	**RAPTOR FPR black** ***Lamp:** Osram Sirius HRI 330W (16.500 Lumens; 7.500°K) ***Optical group:** Beam opening: 0,6° - 3,4°, 50.000 Lux / 15 m, 16-bit motorized linear focus, Linear dimmer / ultra-fast strobe ***Colour generation:** Colour wheel (17 colours + white) with linear, selection for perfect 2-colour beams ***Dynamic effects:** 17-gobo wheel, 8-facet rotating prism ***Filters:** Smooth filter (eliminates the hot spot, evenly diffusing luminosity), Frost filter ***Interface / Control / Programming:** RDM, Wireless ready, Updatable internal operating system ***DMX:** 18 DMX channels ***Pan & Tilt:** 'FPR' system (D.T.S. patent): limitless Pan rotation in both directions, Tri-phase stepper motor technology for ultra-fast silent Pan / Tilt movements, Pan 540°: 2,5 sec.; Tilt 270°: 1,5 sec., 16-bit resolution ***Power supply:** Electronic ballast: 90-260 V 50 / 60 Hz *Power Consumption: 450 W with PFC, Power saving mode (the lamp dims to 80% after shutter closure) ***Weight:** 15,4 Kg ***Connectors:** DMX: 4 x XLR (3-pole In and Out; 5-pole In and Out) connectors by Neutrik; Power supply: POWERCON IN / OUT connectors by Neutrik ***Included items:** 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027), Omega clamp (2 pieces) (cod. 02K00459) ***Packing:** (LxDxH) 590 x 440 x 420 mm 20,3 Kg*	**5 680.00 лв.**	6 816.00 лв.
03.MB005.EB.L	**RAPTOR black** *Same as RAPTOR FPR but without FPR movement *Pan 540° (2,5 sec.); Tilt 270° (1,5 sec.)	**5 280.00 лв.**	6 336.00 лв.
RAL 9003	**.03 WHITE** option — *White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.
	.WS option — *Assembled with Wireless Board + 2 Dbi IP20 Antenna on board **(Extra Cost)***	***304.00 лв.***	364.80 лв.

SPOT

*IP20 (for Indoor installations) — *Moving head projectors

Image	Code	Product	Price	Price
	03.MS011.EB.L	**XR 3000 SPOT CMY black** *With Lamp MSR Gold 1200/2 1200W *85.000 Lux a 5 m (10°) *motorized focus *motorized iris *motorized linear zoom (10°- 35°) *linear dimmer / shutter / strobe (0,85 to 10 flash/sec) *Linear CMY *Colour wheel (7 colours + open) *Customizable rotating gobo wheel (7 gobos) *Customizable fixed gobo wheel (8 gobos) *animation wheel rotating in both directions *3-facet rotating prism *frost filter (soft edge) *LCD graphic display *Wireless ready *Ethernet ready *Updatable Internal operating system *30 DMX channels *Pan 540° (3,9 sec.); Tilt 270° (2,6 sec.) *4 Selectable speed ranges *Pan / Tilt lock *Electronic ballast: 90-260 V 50 / 60 Hz *Power consumption: 1320 W *Power saving mode (the lamp dims to 50% six seconds after shutter closure) *Connectors: DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON connector by Neutrik *Weight 45,5 Kg *Overvoltage circuit protection and overtemperature circuit protection. *International certifications; Safety: EN 60598-1: 1993; EN 60598-2-17: 1989; A1-A3: 1993; EMC: EN 55015 *Included items: 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027)*2 x"C" Clamp G100 black (cod. 0521A015) *Omega clamp (2 pieces) (cod. 02K00467) *Packing: (LxDxH) 670 x 550 x 730 mm 50,5 Kg*	**10 240.00 лв.**	12 288.00 лв.
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.

Image	Code	Product	Price	Price
	03.MS001.L	**XR 8 SPOT black** *With Lamp Philips MSR 575/2 lamp 575W *10.100 Lux at 5 m (11°) *motorized focus *3 selectable zoom angles (11° / 15° / 18°) *linear dimmer / shutter / strobe (0,85 to 10 flash/sec) *8-colour wheels with linear selection for perfect 2-colour beams *customizable rotating gobo wheel (7 gobos) *3-facet rotating prism *frost filter *LED display *Wireless ready *Updatable Internal operating system *20 DMX channels *Pan 540° (3,9 sec.); Tilt 270° (2,6 sec.) *4 Selectable speed ranges *Pan/Tilt locking system *Electro-magnetic ballast; 230 V 50 / 60 Hz *Power consumption: 750 W *Connectors: DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON connector by Neutrik *Weight: 31 Kg *Overvoltage circuit protection and overtemperature circuit protection *International certifications: Safety: EN 60598-1: 1993; EN 60598-2-17: 1989; A1-A3: 1993; EMC: EN 55015 *Included items:*1 x POWERCON male cable connector (cod. 0520P014) *1 x XLR 5 Pins male cable connector (cod. 0508B028) *1 x XLR 5 Pins female cable connector (cod. 0508B027) *GQUICK with "Fast Lock" connection 1/4 turn (cod. 0521A014) *Packing: (LxDxH) 550 x 440 x 800 mm *40 Kg (Electromagnetic ballast)	**4 160.00 лв.**	4 992.00 лв.
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.

Image	Code	Product	Price	Price
	03.MS005.L	**XR 4 SPOT black** *With Lamp GE CSD 250/2SE 250W *5.450 Lux at 5 m (14°) *Motorized focus *14° zoom angle (19° - 22° available) *Linear dimmer / shutter / strobe (0,85 to 10 flash/sec) *8-colour wheel with linear selection for perfect 2-colour beams *customizable rotating gobo wheel (7 gobos) *3-facet rotating prism *LED display *Wireless ready *Updatable Internal operating system *17 DMX channels *Extremely fast rotations: Pan 540° (2,8 sec.); Tilt 270° (2 sec.) *4 Selectable speed ranges *Pan/Tilt locking system *Electro-magnetic ballast; 230 V 50 / 60 Hz *Power consumption: 350 W *Connectors: DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON connector by Neutrik *Weight 26 Kg *Overvoltage circuit protection and overtemperature circuit protection *International certifications: Safety: EN 60598-1: 1993; EN 60598-2-17: 1989; A1-A3: 1993 *EMC: EN 55015 *Included items: *1 x POWERCON male cable connector (cod. 0520P014) *1 x XLR 5 Pins male cable connector (cod. 0508B028) *1 x XLR 5 Pins female cable connector (cod. 0508B027) *GQUICK with "Fast Lock" connection 1/4 turn (cod. 0521A014) *Packing: (LxDxH) 550 x 440 x 800 mm 33 Kg	**3 040.00 лв.**	3 648.00 лв.
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.


WASH

*IP20 (for Indoor installations)

Image	Code	Product	Price	Price
	03.MW005.EB.L	**XR 1200 WASH black** *w/Lamp MSR Gold 1200/2 1200W *55.000 Lux at 5 m (14°) *Fresnel lens Ø 200 mm combined with a dichroic glass reflector *Motorized linear zoom (14°- 26°) *Rotating and indexable beam shaper (0°-180°) *CMY linear system *Colour wheel (8 colours + open) with linear selection for perfect 2-colour beams *2 colour conversion filters (3.200°K / 5.600°K) *LCD display *Wireless ready *Ethernet ready *Updatable Internal operating system *16 DMX channels *Pan 540° (2,9 sec.); Tilt 270° (1,8 sec.) *4 Selectable speed ranges *Pan/Tilt locking system *Electronic ballast; 90-260 V 50 / 60 Hz *Power consumption: 1320 W *Power saving mode (the lamp dims to 50% six seconds after shutter closure) *Connectors: DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON connector by Neutrik *Weight: 38 Kg *Overvoltage circuit protection and overtemperature circuit protection *International certifications: Safety: EN 60598-1: 1993; EN 60598-2-17: 1989; A1-A3: 1993; EMC: EN 55015 *Included items: 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027); 2 x "C" Clamp G100 black (cod. 0521A015) *Omega clamp with ''Fast Lock'' connection 1/4 turn 1 couple (2 pieces) (cod. 02K00467) *Packing: (LxDxH) 580 x 485 x 797 mm 43 Kg	**6 560.00 лв.**	7 872.00 лв.
	03.MW005.EB.PC.L	**XR 1200 WASH PC black** *Same as XR 1200 WASH But with PC lens Ø 150 mm combined with a dichroic glass reflector *104.000 Lux at 5 m (9°) *Motorized linear zoom (9°- 19°)	**6 560.00 лв.**	7 872.00 лв.
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.

*Accessories

*FLIGHTCASES





Code	Description	Note	Price	Price
0521C060.1	2 Units Flightcase for *MAX *Measures: 860x630x850 mm *38 Kg	*High quality *MADE IN ITALY	1 264.00 лв.	1 516.80 лв.
0521C059.1	4 Units Flightcase for *RAPTOR *JACK / PRO *Measures: 860x730x790 mm *42 Kg	*High quality *MADE IN ITALY	1 312.00 лв.	1 574.40 лв.
0521C038.1	2 Units Flightcase for *XR 3000 *XR 2000 / PRO *Measures: 1160x680x885 mm *77 Kg	*High quality *MADE IN ITALY	2 464.00 лв.	2 956.80 лв.
0521C041	1 Units Flightcase for *XR 3000 *XR 2000 / STANDARD		480.00 лв.	576.00 лв.
0521C041.1	1 Units Flightcase for *XR 3000 *XR 2000 / PRO	*High quality *MADE IN ITALY	1 344.00 лв.	1 612.80 лв.
0521C040.1	2 Units Flightcase for *XR 1200 / PRO *Measures: 1160x550x890 mm *42 Kg	*High quality *MADE IN ITALY	1 328.00 лв.	1 593.60 лв.
0521C042.1	1 Unit Flightcase for *XR 1200 / PRO	*High quality *MADE IN ITALY	1 120.00 лв.	1 344.00 лв.
0521C032	2 Units Flightcase for *XR 9/8/5/4 *XR 300 / STANDARD *Measures: 1020x575x772 mm *50 Kg		1 024.00 лв.	1 228.80 лв.
0521C032.1	2 Units Flightcase for *XR 9/8/5/4 *XR 300 / PRO *Measures: 1150x550x900 mm *52 Kg	*High quality *MADE IN ITALY	1 312.00 лв.	1 574.40 лв.

*UPGRADE OPTIC KITS



Code	Description	Price	Price
0506L016	19° OPTIC LENS UPGRADE set *For XR 4 SPOT	19.20 лв.	23.04 лв.
0506L017	22° OPTIC LENS UPGRADE set *For XR 4 SPOT	22.40 лв.	26.88 лв.
02SK0078	KIT LENS UPGRADE From WASH to PC Lenses *For XR 1200 *XR 8 WASH	175.17 лв.	210.20 лв.

*RAINCOVERS



Code	Description	Price	Price
03.MA001	Raincover Ground for *XR 4 *XR 5 *XR 8 *XR 9 *XR 300 *TOP BASES	96.00 лв.	115.20 лв.
03.MA002	Raincover Truss for *XR 4 *XR 5 *XR 8 *XR 9 *XR 300 *BACK BASES	124.80 лв.	149.76 лв.
03.MA009	Raincover Ground for *XR 3000 *XR 2000 *XR 1200 *XR 750 *TOP BASES	134.40 лв.	161.28 лв.
03.MA010	Raincover Truss for *XR 3000 *XR 2000 *XR 1200 *XR 750 *BACK BASES	163.20 лв.	195.84 лв.

*EMBEDDING FLANGES



Code	Description	Price	Price
03.MA007	Embedding Flange *PROFESSIONAL for XR moving heads *Without display *White finishing	281.60 лв.	337.92 лв.
03.MA007.27	Embedding Flange *PROFESSIONAL for XR moving heads *Without display *Black finishing	259.20 лв.	311.04 лв.
03.MA012	Embedding Flange *STANDARD for XR moving heads *Without display *White finishing	108.80 лв.	130.56 лв.

*WIRELESS DMX RETROFIT



Code	Description	Price	Price
03.LA.147	Wireless DMX Receiver Card for *JACK moving head with*INDOOR IP20 2-dBi Antenna	300.80 лв.	360.96 лв.
03.LA.115	Wireless DMX Receiver Card for *XR moving Heads with*INDOOR IP20 2-dBi Antenna	272.00 лв.	326.40 лв.

WONDER *IP20 (for Indoor installations)



!!! NEW !!!

Code	Product	Price	Price with VAT
03.LDR011.FFP	**WONDER FPR black** ***LED Technology:** 49 FULL COLOUR LEDs (RGBW) ***Optical group:** 2 concentric independent high efficiency optical groups, Optical group 1: 3.5°- 52° long excursion linear motorized zoom, Optical group 2: 8°- 52° long excursion linear motorized zoom 20,000 Lux / 5 m (maximum luminosity) ***Color generation:** 4 discrete LED areas; each area is independently controllable (luminosity, colors, effects) 16 million colors each, Wide palette of pure uniform whites with variable / linear color temperature (2700 K - 8000 K) ***Interface / Control / Programming:** LCD graphic display + 4 soft-keys (control /management of the main parameters), RDM, ARTNET available on request, Wireless ready, Updatable internal operating system ***DMX:** 34 DMX channels ***Pan & Tilt** 'FPR' system (D.T.S. patent) Pan (limitless, in both directions); Tilt (270°), Tri-phase stepper motor technology for ultra-fast silent movements, Pan 540°: 2.5 sec.; Tilt 270°: 1.5 sec, 16-bit resolution, Selectable speed ranges, Pan / Tilt lock ***Power supply:** Electronic full-range AC 90-260 V 50/60 Hz ***Power consumption:** 850 W ***Connectors:** DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik, Power supply: POWERCON IN and OUT (re-launch) connectors by Neutrik ***Operating ambient temperature:** -10° / 40° ***Weight:** 23.4 Kg ***International certifications:** Certification CE; LED Class: Class 2 LED product ***Included items:** 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027) *Omega clamp (2 pieces) (cod. 02K00549 *Packing: (LxDxH) x x x x x mm xx Kg	**8 640.00 лв.**	10 368.00 лв.
03.LDR011.F	**WONDER black** *Same as WONDER FPR but without FPR movement *Pan 540° (2 sec.); Tilt 270° (1,2 sec.)	По Запитване	



!!! NEW !!!

Code	Product	Price	Price with VAT
03.LDR012.FFP	**WONDER B FPR black** ***LED Technology:** 49 FULL COLOUR LEDs (RGBW) ***Optical group:** 2: 8°- 52° long excursion linear motorized zoom 20,000 Lux / 5 m (maximum luminosity) ***Color generation:** 4 discrete LED areas; each area is independently controllable (luminosity, colors, effects) 16 million colors each, Wide palette of pure uniform whites with variable / linear color temperature (2700 K - 8000 K) ***Interface / Control / Programming:** LCD graphic display + 4 soft-keys (control /management of the main parameters), RDM, ARTNET available on request, Wireless ready, Updatable internal operating system ***DMX:** 34 DMX channels ***Pan & Tilt** 'FPR' system (D.T.S. patent) Pan (limitless, in both directions); Tilt (270°), Tri-phase stepper motor technology for ultra-fast silent movements, Pan 540°: 2.5 sec.; Tilt 270°: 1.5 sec, 16-bit resolution, Selectable speed ranges, Pan / Tilt lock ***Power supply:** Electronic full-range AC 90-260 V 50/60 Hz ***Power consumption:** 850 W ***Connectors:** DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik, Power supply: POWERCON IN and OUT (re-launch) connectors by Neutrik ***Operating ambient temperature:** -10° / 40° ***Weight:** 23.4 Kg ***International certifications:** Certification CE; LED Class: Class 2 LED product ***Included items:** 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027) *Omega clamp (2 pieces) (cod. 02K00549 *Packing: (LxDxH) x x x x x mm xx Kg	**8 000.00 лв.**	9 600.00 лв.
03.LDR012.F	**WONDER B black** *Same as WONDER FPR but without FPR movement *Pan 540° (2 sec.); Tilt 270° (1,2 sec.)	По Запитване	
RAL 9003	**.03 WHITE** option — *White finishing* ***(Extra Cost)***	***320.00 лв.***	384.00 лв.
	.WS option — *Assembled with Wireless Board + 2 Dbi IP65 Antenna on board* ***(Extra Cost)***	***304.00 лв.***	364.80 лв.

NICK NRG 1201 *IP20 Indoor



Code	Product	Price	Price with VAT
03.LDR006.FFP	**NICK NRG 1201 FPR black** *30 Full Colour LEDs (RGBW) *8°- 50° linear motorized zoom with high efficiency optical system *Uniform projection on surfaces, from very wide Wash to PC Beam *16 million colours *Wide palette of pure uniform whites with variable linear colour temperature (2700°K - 8000°K) *Multi-function OLED graphic colour display + 4 soft keys: control / management / monitoring of the main parameters *Controlled via DMX 512 and RDM standard digital communication protocols *Wireless ready *Ethernet ready *Updatable Internal operating system *20 DMX channels *'FPR': limitless pan rotation, in either direction, never having to reverse motion; Tilt 270° (1,2 sec.) *4 Selectable speed ranges *Electronic full-range AC 90-260 V 50 / 60 Hz *Power consumption: 90 V - 3,7 A - 340 W; 120 V – 2,83 A - 340 W; 230 V – 1,47 A - 340 W ; 260 V – 1,3 A - 340 W *Connectors: DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON IN/OUT connectors by Neutrik *Weight: 11,9 Kg *International certifications: Certification CE; LED Class: Class 2 LED product *Included items: 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027) *"C" Clamp GQUICK with "Fast Lock" connection 1/4 turn (cod. 0521A014) *Packing: (LxDxH) 540 x 435 x 420mm 14,5 Kg	**5 440.00 лв.**	6 528.00 лв.
03.LDR006.F	**NICK NRG 1201 black** *Same as NICK 1201 FPR but without FPR movement *Pan 540° (2 sec.); Tilt 270° (1,2 sec.)	**4 990.00 лв.**	5 988.00 лв.



Code	Product	Price	Price with VAT
03.LDR006.FWFP	**NICK NRG 1201 CT FPR black** *30 Full White LEDs (2700°K - 6500°K) *8°- 50° linear motorized zoom with high efficiency optical system *Uniform projection on surfaces, from very wide Wash to PC Beam *Wide palette of pure uniform whites with variable linear colour temperature (2700°K - 8000°K) *Multi-function OLED graphic colour display + 4 soft keys: control / management / monitoring of the main parameters *Controlled via DMX 512 and RDM standard digital communication protocols *Wireless ready *Ethernet ready *Updatable Internal operating system *20 DMX channels *'FPR': limitless pan rotation, in either direction, never having to reverse motion; Tilt 270° (1,2 sec.) *4 Selectable speed ranges *Electronic full-range AC 90-260 V 50 / 60 Hz *Power consumption: 90 V - 3,7 A - 340 W; 120 V – 2,83 A - 340 W; 230 V – 1,47 A - 340 W; 260 V – 1,3 A - 340 W *Connectors: DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON IN/OUT connectors by Neutrik *Weight: 11,90 Kg *International certifications: Certification CE; LED Class: Class 2 LED product *Included items: 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027) *"C" Clamp GQUICK with "Fast Lock" connection 1/4 turn (cod. 0521A014) *Packing: (LxDxH) 540 x 435 x 420mm 14,5 Kg	**5 500.00 лв.**	6 600.00 лв.
03.LDR006.FW	**NICK NRG 1201 CT black** *Same as NICK 1201 CT FPR but without FPR movement *Pan 540° (2 sec.); Tilt 270° (1,2 sec.)	**5 085.00 лв.**	6 102.00 лв.
RAL 9003	**.03 WHITE** option — *White finishing* ***(Extra Cost)***	***320.00 лв.***	384.00 лв.
	.WS option — *Assembled with Wireless Board + 2 Dbi IP65 Antenna on board* ***(Extra Cost)***	***304.00 лв.***	364.80 лв.

NICK NRG 501 *IP20 Indoor



!!! NEW !!!

Code	Product	Price	Price
03.LDR009.FFP	**NICK NRG 501 FPR black** ***LED Technology:** 7 FULL COLOUR LEDs (RGBW) *Optical group: 3,5°- 52° linear motorized zoom with high-efficiency optical system, Uniform projection on surfaces, from very wide Wash to PC Beam ***Colour generation:** 16 million colours, Wide palette of pure uniform whites with variable linear colour temperature (2700°K - 8000°K) ***Interface / Control / Programming:** Multi-function OLED graphic display,Wireless ready, Updatable internal operating system ***DMX:** 20 DMX channels ***Pan & Tilt:** Tri-phase stepper motor technology for ultra-fast silent Pan / Tilt movements, Pan 540°: 2,5 sec.; Tilt 270°: 1,5 sec. 16-bit resolution, Also available with 'FPR' system (D.T.S. patent): limitless Pan rotation in both directions ***Power supply:** Electronic full-range AC 90-260 V 50/60 Hz ***Power consumption:** 125 W ***Weight:** 8,9 Kg ***Connectors:** DMX: 4 x XLR (3 and 5-pole In / Out) *Powercon In / Out ***Certification:** *Multi-function OLED graphic display : CE; LED Class: Class 2 LED product ***Included items:** 1 x POWERCON male connector; 1 x XLR 5 Pins male connector ; 1 x XLR 5 Pins female connector; 1 x "C" Clamp GQUICK ***Packing:** (LxDxH) 460 x 365 x 320 mm *10,9 Kg	**3 425.00 лв.**	4 110.00 лв.
03.LDR009.F	**NICK NRG 501 black** *Same as NICK 501 FPR but without FPR movement *Pan 540° (2 sec.); Tilt 270° (1,2 sec.)	**3 025.00 лв.**	3 630.00 лв.



!!! NEW !!!

Code	Product	Price	Price
03.LDR009.FWFP	**NICK NRG 501 CT FPR black** ***LED Technology:** 7 Full White LEDs (2700°K - 6500°K) *Optical group: 3,5°- 52° linear motorized zoom with high-efficiency optical system, Uniform projection on surfaces, from very wide Wash to PC Beam ***Colour generation:** 16 million colours, Wide palette of pure uniform whites with variable linear colour temperature (2700°K - 8000°K) ***Interface / Control / Programming:** Multi-function OLED graphic display,Wireless ready, Updatable internal operating system ***DMX:** 20 DMX channels ***Pan & Tilt:** Tri-phase stepper motor technology for ultra-fast silent Pan / Tilt movements, Pan 540°: 2,5 sec.; Tilt 270°: 1,5 sec. 16-bit resolution, Also available with 'FPR' system (D.T.S. patent): limitless Pan rotation in both directions ***Power supply:** Electronic full-range AC 90-260 V 50/60 Hz ***Power consumption:** 125 W ***Weight:** 8,9 Kg ***Connectors:** DMX: 4 x XLR (3 and 5-pole In / Out) *Powercon In / Out ***Certification:** *Multi-function OLED graphic display : CE; LED Class: Class 2 LED product ***Included items:** 1 x POWERCON male connector; 1 x XLR 5 Pins male connector ; 1 x XLR 5 Pins female connector; 1 x "C" Clamp GQUICK ***Packing:** (LxDxH) 460 x 365 x 320 mm *10,9 Kg	**3 425.00 лв.**	4 110.00 лв.
03.LDR009.FW	**NICK NRG 501 CT black** *Same as NICK 501 CT FPR but without FPR movement *Pan 540° (2 sec.); Tilt 270° (1,2 sec.)	**3 025.00 лв.**	3 630.00 лв.

	Option	Description	Price	Price
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***192.00 лв.***	230.40 лв.
	.WS option	*Assembled with Wireless Board + 2 Dbi IP65 Antenna on board **(Extra Cost)***	***304.00 лв.***	364.80 лв.

NICK NRG 1200 *IP20 (for Indoor installations)



NICK NRG 1200 *black

*30 Full Colour LEDs (RGBW) * Three interchangeable lenses sets: Spot, Medium Flood and Wide *Uniform projection on surfaces *16 million colours *Wide palette of pure uniform whites with variable linear colour temperature (2700°K - 8000°K) *Multi-function OLED graphic colour display + 4 soft keys: control / management / monitoring of the main parameters *Controlled via DMX 512 and RDM standard digital communication protocols *Wireless ready *Ethernet ready *Updatable Internal operating system *20 DMX channels *Ultra-fast movement: Pan 540° (2 sec.); Tilt 270° (1,2 sec.) *4 Selectable speed ranges *Electronic full-range AC 90-260 V 50 / 60 Hz *Power consumption: 90 V - 3,7 A - 340 W; 120 V – 2,83 A - 340 W; 230 V – 1,47 A - 340 W; 260 V – 1,3 A - 340 W *Connectors: DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON IN/OUT connectors by Neutrik *Weight: 10,5 Kg *International certifications: Certification CE; LED Class: Class 2 LED product *Included items: 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027) *"C" Clamp GQUICK with "Fast Lock" connection 1/4 turn (cod. 0521A014)

Code	Lens	Price	Price
03.LDR008.F12	*SPOT lens *10°	**3 920.00 лв.**	4 704.00 лв.
03.LDR008.F25	*MEDIUM FLOOD lens *25°	**3 920.00 лв.**	4 704.00 лв.
03.LDR008.F45	*WIDE lens *45°	**3 920.00 лв.**	4 704.00 лв.



NICK NRG 1200 *CT *black

*Same as NICK NRG 1200 but with *30 Full White LEDs
(Variable temperature from 2700K to 6500K)
* Three interchangeable lenses sets: Spot, Medium Flood and Wide

Code	Lens	Price	Price
03.LDR008.FW12	*SPOT lens *10°	**3 920.00 лв.**	4 704.00 лв.
03.LDR008.FW25	*MEDIUM FLOOD lens *25°	**3 920.00 лв.**	4 704.00 лв.
03.LDR008.FW45	*WIDE lens *45°	**3 920.00 лв.**	4 704.00 лв.

NICK NRG 1200 *WARM WHITE *black

*Same as NICK NRG 1200 but with *30 Warm White LEDs (3200K)
*Three interchangeable lenses sets: Spot, Medium Flood and Wide

Code	Lens	Price	Price
	*SPOT lens *10°	**3 920.00 лв.**	4 704.00 лв.
	*MEDIUM FLOOD lens *25°	**3 920.00 лв.**	4 704.00 лв.
	*WIDE lens *45°	**3 920.00 лв.**	4 704.00 лв.

NICK NRG 1200 *COLD WHITE *black

*Same as NICK NRG 1200 but with *30 Full Cold White LEDs (6500K)
*Three interchangeable lenses sets: Spot, Medium Flood and Wide

Code	Lens	Price	Price
	*SPOT lens *10°	**3 920.00 лв.**	4 704.00 лв.
	*MEDIUM FLOOD lens *25°	**3 920.00 лв.**	4 704.00 лв.
	*WIDE lens *45°	**3 920.00 лв.**	4 704.00 лв.

	Option	Description	Price	Price
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.
	.WS option	*Assembled with Wireless Board + 2 Dbi IP65 Antenna on board **(Extra Cost)***	***304.00 лв.***	364.80 лв.

LED WASHERS

ENTERTAINMENT

NICK 600 FC


*IP20 (for Indoor installations)



NICK 600 *FC *black

*30 Full Colour LEDs (RGBW) * Three interchangeable lenses sets: Spot, Medium Flood and Wide *Uniform projection on surfaces *16 million colours *Wide palette of pure uniform whites with variable linear colour temperature (2700°K - 8000°K) *Multi-function OLED graphic colour display + 4 soft keys: control / management / monitoring of the main parameters *Controlled via DMX 512 and RDM standard digital communication protocols *Wireless ready *Ethernet ready *Updatable Internal operating system *20 DMX channels *Ultra-fast movement: Pan 540° (2 sec.); Tilt 270° (1,2 sec.) *4 Selectable speed ranges *Electronic full-range AC 90-260 V 50 / 60 Hz *Power consumption: 90 V - 3,7 A - 340 W; 120 V – 2,83 A - 340 W; 230 V – 1,47 A - 340 W; 260 V – 1,3 A - 340 W *Connectors: DMX: 4 XLR connectors (3-pole In and Out; 5-pole In and Out) by Neutrik; Power supply: POWERCON IN/OUT connectors by Neutrik *Weight: 10,5 Kg *International certifications: Certification CE; LED Class: Class 2 LED product *Included items: 1 x POWERCON male cable connector (cod. 0520P014); 1 x XLR 5 Pins male cable connector (cod. 0508B028); 1 x XLR 5 Pins female cable connector (cod. 0508B027) *"C" Clamp GQUICK with "Fast Lock" connection 1/4 turn (cod. 0521A014)

Code	Lens	Price	Price
03.LDR005.F12	*SPOT lens *10°	**3 072.00 лв.**	3 686.40 лв.
03.LDR005.F25	*MEDIUM FLOOD lens *25°	**3 072.00 лв.**	3 686.40 лв.
03.LDR005.F45	*WIDE lens *45°	**3 072.00 лв.**	3 686.40 лв.




Option	Description	Price	Price
.WS option	*Assembled with Wireless Board + 2 Dbi IP65 Antenna on board* ***(Extra Cost)***	***304.00 лв.***	364.80 лв.

*Accessories

*NICK

*FLIGHTCASES



Code	Description	Note	Price	Price
0521C061.1	2 Units Flightcase for *WONDER *Measures: x x x x x mm *xx Kg	*High quality *MADE IN ITALY	**1 504.00 лв.**	1 804.80 лв.
0521C059.1	4 Units Flightcase for *NICK NRG 1201 / PRO *Measures: 860x730x790 mm *xx Kg	*High quality *MADE IN ITALY	**1 312.00 лв.**	1 574.40 лв.
0521C062.1	6 Units Flightcase for *NICK NRG 501 / PRO *Measures: x x x x x mm *xx Kg	*High quality *MADE IN ITALY	**1 312.00 лв.**	1 574.40 лв.

*KIT LENSES



Code	Description	Lens	Price	Price
03.LK.110	**Lenses Set for** *NICK NRG 1200 *NICK NRG 1200 CT *NICK 1200 WARM WHITE *NICK 1200 COLD WHITE	*SPOT (10°)	**288.00 лв.**	345.60 лв.
03.LK.111		*MEDIUM FLOOD (25°)	**288.00 лв.**	345.60 лв.
03.LK.112		*WIDE FLOOD (45°)	**288.00 лв.**	345.60 лв.



Code	Description	Lens	Price	Price
03.LK.101	**Lenses Set for** *NICK 600 FC	*SPOT (10°)	**304.00 лв.**	364.80 лв.
03.LK.102		*MEDIUM FLOOD (25°)	**272.00 лв.**	326.40 лв.
03.LK.103		*WIDE FLOOD (45°)	**272.00 лв.**	326.40 лв.

*WIRELESS DMX RETROFIT



Code	Description	Price	Price
03.LA.146	Wireless DMX Receiver Card for *NICK NRG 1201 / 501 with *INDOOR IP20 2-dBi Antenna	**300.80 лв.**	360.96 лв.

DELTA 8 R

*IP65 (for Outdoor installations)



DELTA 8 R *FC *black

*NEW 36 x 3W Full Colour RGBW *RGB colour generation (16 million colours) *3 different colour mixing modes: RGB, CMY, HSV *Colour temperature variable on a linear range (2800°K ÷ 6500°K) *Dedicated DMX "White" channel *LEDs average lifespan: 50.000 hours *No infrared emission; no ultraviolet emission *3 different lenses sets are available (Spot, Medium flood, Wide flood)
*LED display *Fully programmable via built-in user interface *Master or Slave capability (chains of up to 32 interconnected units) *Remotely controlled by cable or wireless *USITT DMX 512 protocol. *15 DMX channels *Movement on 2 axes: *320° horizontal (1,66 sec MOTORIZED) *180° vertical 1 (2,18 sec MOTORIZED) *IP65 protection level *Connection: Power Supply: cable gland 2 m (3 x 1,5 sq mm) *DMX IN/OUT: 5-pole M+F XLR connectors + 0,5 m cable (IP20) *Full range AC 90-260V 50-60 Hz power supply *Consumption: * 90 V - 3 A - 270 W *20 V - 2,5 A - 270 W *230 V -1,17 A - 270 W *260 V - 1 A - 270 W *Weight: 24 Kg • Included items: 2 x “C” Clamp GQUICK *Packing: (LxDxH) 530x485x660 mm *30 kg


Code	Lens	Price	Price
03.LDR010.F08	*SPOT lens *8°	**4 448.00 лв.**	5 337.60 лв.
03.LDR010.F25	*MEDIUM FLOOD lens *25°	**4 448.00 лв.**	5 337.60 лв.
03.LDR010.F40	*WIDE lens *40°	**4 448.00 лв.**	5 337.60 лв.



DELTA 8 R *CT *black

*NEW 36 x 3W Full White (2.700 K-6.500 K) *Colour temperature variable on a linear range (2700°K ÷ 6500°K) *Dedicated DMX "White" channel *LEDs average lifespan: 50.000 hours *No infrared emission; no ultraviolet emission *3 different lenses sets are available (Spot, Medium flood, Wide flood) *LED display *Fully programmable via built-in user interface *Master or Slave capability (chains of up to 32 interconnected units) *Remotely controlled by cable or wireless *USITT DMX 512 protocol. *15 DMX channels *Movement on 2 axes: *320° horizontal (1,66 sec MOTORIZED) *180° vertical 1 (2,18 sec MOTORIZED) *IP65 protection level *Connection: Power Supply: cable gland 2 m (3 x 1,5 sq mm) *DMX IN/OUT: 5-pole M+F XLR connectors + 0,5 m cable (IP20) *Full range AC 90-260V 50-60 Hz power supply *Consumption: * 90 V - 3 A - 270 W *20 V - 2,5 A - 270 W *230 V -1,17 A - 270 W *260 V - 1 A - 270 W *Weight: 24 Kg • Included items: 2 x “C” Clamp GQUICK *Packing: (LxDxH) 530x485x660 mm *30 kg

Code	Lens	Price	Price
DELTA8R-FWHITE-SP	*SPOT lens *8°	**4 512.00 лв.**	5 414.40 лв.
DELTA8R-FWHITE-MFL	*MEDIUM FLOOD lens *25°	**4 512.00 лв.**	5 414.40 лв.
DELTA8R-FWHITE-WFL	*WIDE lens *40°	**4 512.00 лв.**	5 414.40 лв.

	Option	Description	Price	Price
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.
	**.WS** option	*Assembled with Wireless Board + 2 Dbi IP65 Antenna on board **(Extra Cost)***	***304.00 лв.***	364.80 лв.

*Accessories

DELTA 8 R

*KIT LENSES



Lenses Set for: *DELTA 8 R FC (Full Colour RGBW) *DELTA 8 R CT (Full White)

Code	Type	Price	Price
03.LK.098	*SPOT (10°)	**384.00 лв.**	460.80 лв.
03.LK.099	*MEDIUM FLOOD (25°)	**288.00 лв.**	345.60 лв.
03.LK.100	*WIDE FLOOD (40°)	**384.00 лв.**	460.80 лв.

*BARNDOOR



Code	Description	Price	Price
03.LA.057	Barndoor for *DELTA 12 / DELTA 8 Black	**208.00 лв.**	249.60 лв.

*WIRELESS DMX RETROFIT



Code	Description	Price	Price
03.LA.122	Wireless DMX Receiver Card for *DELTA 8 Line with *OUTDOOR IP20 2-dBi Antenna	**320.00 лв.**	384.00 лв.

*FIXING BRACKET



Code	Description	Price
03.LK.007	Fixing bracket for DELTA 8 for installation on Groundor Wall	33.00 лв.

DELTA 12 *IP65 (for Outdoor installations)



!!! NEW !!!

DELTA 12 *FC *black

*48 LEDs Full Colour RGBW *16 million colours *CRI > 90 *Variable linear colour temperature (2700 K - 8000 K) *Uniform projection on surfaces *dedicated DMX channel for custom whites *Four interchangeable lenses sets available: (22.050 Lux at 5 m); Narrow (12.900 Lux at 5 m); Medium flood (2200 Lux at 5 m); Wide flood (1400 Lux at 5 m) *8 additional optional holographic filters available (user interchangeable): 10° / 20° / 30° / 40° / 60° / 80° / 60° x 10° / 75° x 45° *7 segments display + 4 soft keys. *Controlled via DMX 512 standard digital communication protocols *Wireless ready *Ethernet ready *Internal updatable operating system *10 DMX channels *Twilight sensor for switching the unit on and off automatically, according to external light intensity *Playback of a pre-programmed sequence of events over an entire week. *Manual movement on axis (Tilt 270°) *Protection: IP65 protection level against the penetration of solids and liquids *Full-Range AC 90-260 V 50/60 Hz *Power consumption *500W *Included items: OMEGA 10 Fixing Bracket; 1 x User's manual *Weight: 18 Kg *Packing: (LxDxH) 630 x 500 x 660 mm *20 Kg

Code	Lens	Price	Price
03.LDF006.F08	*SUPER-NARROW lens *8°	**4 352.00 лв.**	5 222.40 лв.
03.LDF006.F12	*SPOT lens *10°	**4 352.00 лв.**	5 222.40 лв.
03.LDF006.F25	*MEDIUM FLOOD lens *23°	**4 352.00 лв.**	5 222.40 лв.
03.LDF006.F45	*WIDE lens *42°	**4 352.00 лв.**	5 222.40 лв.



!!! NEW !!!

DELTA 12 *CT *black

*48 LEDs Full WHITE *CRI > 90 *Variable linear colour temperature (2700 K - 8000 K) *Uniform projection on surfaces *dedicated DMX channel for custom whites *Four interchangeable lenses sets available: (22.050 Lux at 5 m); Narrow (12.900 Lux at 5 m); Medium flood (2200 Lux at 5 m); Wide flood (1400 Lux at 5 m) *8 additional optional holographic filters available (user interchangeable): 10° / 20° / 30° / 40° / 60° / 80° / 60° x 10° / 75° x 45° *7 segments display + 4 soft keys. *Controlled via DMX 512 standard digital communication protocols *Wireless ready *Ethernet ready *Internal updatable operating system *10 DMX channels *Twilight sensor for switching the unit on and off automatically, according to external light intensity *Playback of a pre-programmed sequence of events over an entire week. *Manual movement on axis (Tilt 270°) *Protection: IP65 protection level against the penetration of solids and liquids *Full-Range AC 90-260 V 50/60 Hz *Power consumption *500W *Included items: OMEGA 10 Fixing Bracket; 1 x User's manual *Weight: 18 Kg *Packing: (LxDxH) 630 x 500 x 660 mm *20 Kg

Code	Lens	Price	Price
03.LDF006.FW08	*SUPER-NARROW lens *8°	**4 624.00 лв.**	5 548.80 лв.
03.LDF006.FW12	*SPOT lens *10°	**4 624.00 лв.**	5 548.80 лв.
03.LDF006.FW25	*MEDIUM FLOOD lens *23°	**4 624.00 лв.**	5 548.80 лв.
03.LDF006.FW45	*WIDE lens *42°	**4 624.00 лв.**	5 548.80 лв.

	Option	Description	Price	Price
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***320.00 лв.***	384.00 лв.
	.WS option	*Assembled with Wireless Board + 2 Dbi IP65 Antenna on board **(Extra Cost)***	***288.00 лв.***	345.60 лв.

*Accessories DELTA 12

*HOLOGRAPHIC FILTERS



Code	Description		Price	Price
03.LA.123	FRAME SET needed for Mounting Holografic Filters on the external protection glass of DELTA 12 F SUPER-NARROW Lens		**89.60 лв.**	107.52 лв.
0506A042	Holographic Filter for *DELTA 12 *10° FWHM	*1 pcs each DELTA 12	**105.60 лв.**	126.72 лв.
0506A043	Holographic Filter for *DELTA 12 *20° FWHM		**105.60 лв.**	126.72 лв.
0506A044	Holographic Filter for *DELTA 12 *30° FWHM		**105.60 лв.**	126.72 лв.
0506A045	Holographic Filter for *DELTA 12 *40° FWHM		**105.60 лв.**	126.72 лв.
0506A046	Holographic Filter for *DELTA 12 *60° FWHM		**105.60 лв.**	126.72 лв.
0506A047	Holographic Filter for *DELTA 12 *80° FWHM		**105.60 лв.**	126.72 лв.
0506A048	Holographic Filter for *DELTA 12 *10° x 60° FWHM *(60° Vertical x 10° horizontal)		**105.60 лв.**	126.72 лв.
0506A049	Holographic Filter for *DELTA 12 *75° x 45° FWHM *(75° Vertical x 45° horizontal)		**105.60 лв.**	126.72 лв.

*KIT LENSES



Kit Lens for:
*DELTA 12 FC (Full colour RGBW) *DELTA 12 CT (Full White)

Code	Lens	Price	Price
03.LK.130	*SUPER NARROW (8°)	**489.60 лв.**	587.52 лв.
03.LK.127	*SPOT (10°)	**489.60 лв.**	587.52 лв.
03.LK.128	*MEDIUM FLOOD (23°)	**489.60 лв.**	587.52 лв.
03.LK.129	*WIDE FLOOD (42°)	**489.60 лв.**	587.52 лв.

*BARNDOOR




Code	Description	Price	Price
03.LA.057	Barndoor for *DELTA 12 Black	**208.00 лв.**	249.60 лв.

*OMEGA CLAMP



Code	Description	Price	Price
02K00523	Omega 12 fixing Bracket with "Fast Lock" connection 1⁄4 turn, for *DELTA 12 F Line (Already included in the DELTA 12 cardboard)	**51.20 лв.**	61.44 лв.


FOS 100 POWER SOLO *IP20 (for Indoor installations)



FOS 100 POWER SOLO *IP20 *FC *black

*Thanks to its powerful flux this bar is ideal for lighting and colouring with an even projection building facades, public and commercial places, as well as shows and events
*NEW 24 Full Colour (RGBW) LEDs *7.028 Lux at 3m*16 million colours; linear colour temperature 2800°K ÷ 6500°K
*No infrared emission; no ultraviolet emission; LEDs average lifespan: 50.000 hours
*3 lenses sets available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lightingconsole (USITT DMX 512 serial digital protocol) *IP20 protection level against the penetration of solids and liquids * FOS units are made on aluminum and steel *Electronic full range power supply 90-260V - AC/50-60 Hz *Integrated power supply *Consumption: 200 W max • Connection: M16 male connector + cable (30cm) *Packing (LxDxH) 1060 x 160 x 200 mm *8,5 Kg

Code	Lens	Price	Price
03.LB030S.F10	*SPOT lens *15°	**2 432.00 лв.**	2 918.40 лв.
03.LB030S.F25	*MEDIUM FLOOD lens *28°	**2 432.00 лв.**	2 918.40 лв.
03.LB030S.F40	*WIDE lens *42°	**2 432.00 лв.**	2 918.40 лв.



FOS 100 POWER SOLO *IP20 *CT *black

*Thanks to its powerful flux this bar is ideal for lighting and colouring with an even projection building facades, public and commercial places, as well as shows and events
*NEW 24 Full White (White+Amber) LEDs x Lux at 3m; linear colour temperature 2800°K ÷ 6500°K
*3 lenses sets available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lightingconsole (USITT DMX 512 serial digital protocol) *IP20 protection level against the penetration of solids and liquids * FOS units are made on aluminum and steel *Electronic full range power supply 90-260V - AC/50-60 Hz *Integrated power supply *Consumption: 200 W max • Connection: M16 male connector + cable (30cm) *Packing (LxDxH) 1060 x 160 x 200 mm *8,5 Kg

Code	Lens	Price	Price
03.LB030S.FW10	*SPOT lens *15°	**2 560.00 лв.**	3 072.00 лв.
03.LB030S.FW25	*MEDIUM FLOOD lens *28°	**2 560.00 лв.**	3 072.00 лв.
03.LB030S.FW40	*WIDE lens *42°	**2 560.00 лв.**	3 072.00 лв.

*Accessories for FOS 100 POWER


*KIT LENSES



Kit Lens for: (*2 sets needed each FOS 100 POWER)
*FOS 100 POWER FC (Full Colour RGBW) *FOS 100 POWER CT (Full White)

Code	Type	Price	Price
03.LK.107	*SPOT (15°) ***BLACK**	**131.20 лв.**	157.44 лв.
03.LK.108	*MEDIUM FLOOD (28°) ***BLACK**	**105.60 лв.**	126.72 лв.
03.LK.109	*WIDE FLOOD (42°) ***BLACK**	**131.20 лв.**	157.44 лв.

*BARNDOOR



Code	Description	Finishing	Price	Price
03.LA.142	BARNDOOR for FOS *Price for 1 modular Kit ***3 Kits for FOS 100 POWER** ***3 Kits for FOS 100**	***BLACK finishing**	**57.60 лв.**	69.12 лв.

*CLAMPS / SAFETY WIRE



Code	Description	Price	Price
0521A004	G60 "C" Clamp (Max. load 50 Kg) *For Ø50mm tubes *Black recommended for *FOR 100 SOLO POWER	**15.00 лв.**	18.00 лв.
0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black recommended for *FOR 100 SOLO POWER	**13.76 лв.**	16.51 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

FOS 100 DYNAMIC SOLO *IP20 (for Indoor installations)



Code	Description	Lens	Price	Price with VAT
03.DYN008S.F10	**FOS 100 SOLO *IP20 *DYNAMIC *black** *Thanks to its powerful flux this bar is ideal for lighting and colouring building facades, public and commercial places with an even projection. ***NEW** 15 Full Colour RGBW LEDs 3W **with Dynamic control** *16 million colours; linear colour temperature 2800°K ÷ 6500°K; 16 selectable types of white No infrared emission; no ultraviolet emission LEDs average lifespan: 50.000 hours *3 lenses sets available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lighting console (USITT DMX 512 serial digital protocol) *IP20 (INDOOR) protection level against the penetration of solids and liquids *FOS units are made on aluminum and steel *Power supply: Z10 DYNAMIC full-range power supply / controller; 90-260 V - AC/50-60 Hz *Consumption: *90 V - 0,78 A - 70 W *120 V - 0,58 A - 70 W *208 V - 0,36 A - 70 W *230 V - 0,30 A - 70 W *Connections: M12 5 pins male connector + cable (35 cm) *Included items: M12 8 pins female connector *Weight: 6,5 Kg *Packing: (LxHxD) 1057 x 158 x 187 mm *8,5 Kg	*SPOT lens *15°	**2 483.20 лв.**	2 979.84 лв.
03.DYN008S.F25		*MEDIUM FLOOD lens *28°	**2 483.20 лв.**	2 979.84 лв.
03.DYN008S.F40		*WIDE lens *42°	**2 483.20 лв.**	2 979.84 лв.

FOS 100 SOLO *IP20 (for Indoor installations)



Code	Description	Lens	Price	Price with VAT
03.LB033S.F10	**FOS 100 SOLO *IP20 *FC *black** *Thanks to its powerful flux this bar is ideal for lighting and colouring building facades, public and commercial places with an even projection ***NEW** 15 Full Colour RGBW; 16 million colours; linear colour temperature 2800°K ÷ 6500°K; 16 selectable types of white *No infrared emission; no ultraviolet emission; LEDs average lifespan: 50.000 hours *3 lenses sets available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lightingconsole (USITT DMX 512 serial digital protocol) *IP20 (INDOOR) protection level *FOS units are made on aluminum and steel *Integrated power supply ('SOLO' version) *Included items: M12 8 pins female connector *Weight: 7,1 Kg *Consumption: 70 W *Connection: M12 8 pins male connector + cable (35 cm) *Packing: (LxDxH) 1060 x 160 x 200 mm *8,5 Kg	*SPOT lens *15°	**1 824.00 лв.**	2 188.80 лв.
03.LB033S.F25		*MEDIUM FLOOD lens *28°	**1 824.00 лв.**	2 188.80 лв.
03.LB033S.F40		*WIDE lens *42°	**1 824.00 лв.**	2 188.80 лв.



Code	Description	Lens	Price	Price with VAT
F100S-RGBW-IP20-SP	**FOS 100 SOLO *IP20 *RGBW *black** *Thanks to its powerful flux this bar is ideal for lighting and colouring building facades, public and commercial places with an even projection ***NEW** 48 LEDs: 12 x Red, 12 x Green, 12 x Blue, 12 x White 1W P4 type LEDs; 16 million colours; linear colour temperature 2800°K ÷ 6500°K; 16 selectable types of white *No infrared emission; no ultraviolet emission; LEDs average lifespan: 50.000 hours *3 lenses sets available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lightingconsole (USITT DMX 512 serial digital protocol) *IP20 (INDOOR) protection level *FOS units are made on aluminum and steel *Integrated power supply ('SOLO' version) *Included items: M12 8 pins female connector *Weight: 7,1 Kg *Consumption: 70 W *Connection: M12 8 pins male connector + cable (35 cm) *Packing: (LxDxH) 1060 x 160 x 200 mm *8,5 Kg	*SPOT lens *15°	**1 664.00 лв.**	1 996.80 лв.
F100S-RGBW-IP20-MFL		*MEDIUM FLOOD lens *28°	**1 664.00 лв.**	1 996.80 лв.
F100S-RGBW-IP20-WFL		*WIDE lens *42°	**1 664.00 лв.**	1 996.80 лв.



Code	Description	Lens	Price	Price with VAT
03.LB033S.FW10	**FOS 100 SOLO *IP20 *CT *black** *Thanks to its powerful flux this bar is ideal for lighting and colouring building facades, public and commercial places with an even projection ***NEW** 15 Full White (White+Amber) linear colour temperature 2800°K ÷ 6500°K; 16 selectable types of white *No infrared emission; no ultraviolet emission; LEDs average lifespan: 50.000 hours *3 lenses sets available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lightingconsole (USITT DMX 512 serial digital protocol) *IP20 (INDOOR) protection level *FOS units are made on aluminum and steel *Integrated power supply ('SOLO' version) *Included items: M12 8 pins female connector *Weight: 7,1 Kg *Consumption: 70 W *Connection: M12 8 pins male connector + cable (35 cm) *Packing: (LxDxH) 1060 x 160 x 200 mm *8,5 Kg	*SPOT lens *15°	**1 904.00 лв.**	2 284.80 лв.
03.LB033S.FW25		*MEDIUM FLOOD lens *28°	**1 904.00 лв.**	2 284.80 лв.
03.LB033S.FW40		*WIDE lens *42°	**1 904.00 лв.**	2 284.80 лв.


*Accessories — FOS

*KIT LENSES



Code	Description	Type	Price	Price with VAT
03.LK.060.N	**Kit Lens for:** (*3 sets needed each FOS 100) *FOS 100 FC (Full Colour RGBW) *FOS 100 CT (Full White) ***BLACK finishing**	*SPOT (15°)	**70.40 лв.**	84.48 лв.
03.LK.061.N		*MEDIUM FLOOD (28°)	**54.40 лв.**	65.28 лв.
03.LK.062.N		*WIDE FLOOD (42°)	**70.40 лв.**	84.48 лв.

*BARNDOOR



Code	Description	Price	Price with VAT
03.LA.142	BARNDOOR for FOS *Black finishing *Price for 1 pcs *Modular: *3 Kits for FOS 100 *2 Kits for FOS 66 *1 Kit for FOS 33	**57.60 лв.**	69.12 лв.

*CLAMPS / SAFETY WIRE



Code	Description	Price	Price with VAT
0521A004	G60 "C" Clamp (Max. load 50 Kg) *For Ø50mm tubes *Black recommended for *FOS 100 SOLO	**15.00 лв.**	18.00 лв.
0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black recommended for *FOS 100 SOLO	**13.76 лв.**	16.51 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

TITAN SOLO *IP20 (for Indoor installations)



TITAN SOLO *IP20 *FC *grey glitter

*NEW 15 x Full Colour RGBW LEDs *16 million colours; linear colour temperature 2800°K ÷ 6500°K *16 selectable types of White • no infrared emission; no ultraviolet emission *LEDs average lifespan: 50.000 hours *3 lenses set available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lighting console (USITT DMX 512 serial digital protocol) *IP20 (INDOOR) protection level against the penetration of solids and liquids *TITAN is made on aluminium *Integrated full-range power supply / controller *Consumption: xW *Connection: M12 8 pins male connector + cable 100 cm connection system *Powerconn + 5-pin and 3-pin XLR connectors *Included items: M12 8 pins female connector *Weight 6,4 Kg *Packing: (LxDxH) 293 x 250 x 353 mm *7,7 Kg

Code	Lens	Price	Price
03.LDB153S.F10	*SPOT lens *10°	**1 536.00 лв.**	1 843.20 лв.
03.LDB153S.F25	*MEDIUM FLOOD lens *27°	**1 536.00 лв.**	1 843.20 лв.
03.LDB153S.F40	*WIDE lens *40°	**1 536.00 лв.**	1 843.20 лв.



TITAN SOLO *IP20 *RGBW *grey glitter

*NEW 48 RGBW LEDs: 12 x Red, 12 x Green, 12 x Blue, 12 x White; 16 million colours; linear colour temperature 2800°K ÷ 6500°K; *16 selectable types of White • no infrared emission; no ultraviolet emission *LEDs average lifespan: 50.000 hours *3 lenses set available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lighting console (USITT DMX 512 serial digital protocol) *IP20 (INDOOR) protection level against the penetration of solids and liquids *TITAN is made on aluminium *Integrated full-range power supply / controller *Consumption: xW *Connection: M12 8 pins male connector + cable 100 cm connection system *Powerconn + 5-pin and 3-pin XLR connectors *Included items: M12 8 pins female connector *Weight 6,4 Kg *Packing: (LxDxH) 293 x 250 x 353 mm *7,7 Kg

Code	Lens	Price	Price
03.LDB153S.T10	*SPOT lens *8°	**1 424.00 лв.**	1 708.80 лв.
03.LDB153S.T25	*MEDIUM FLOOD lens *25°	**1 424.00 лв.**	1 708.80 лв.
03.LDB153S.T40	*WIDE lens *40°	**1 424.00 лв.**	1 708.80 лв.



TITAN SOLO *IP20 *CT *grey glitter

*NEW 15 x Full White (2.700 K-6.500 K) LEDs *linear colour temperature 2800°K ÷ 6500°K *16 selectable types of White •no infrared emission; no ultraviolet emission *LEDs average lifespan: 50.000 hours *3 lenses set available (Spot, Medium flood, Wide flood) *Master or Slave capability (chains of up to 32 interconnected units) *Control Via any DMX lighting console (USITT DMX 512 serial digital protocol) *IP20 (INDOOR) protection level against the penetration of solids and liquids *TITAN is made on aluminium *Integrated full-range power supply / controller *Consumption: xW *Connection: M12 8 pins male connector + cable 100 cm connection system *Powerconn + 5-pin and 3-pin XLR connectors *Included items: M12 8 pins female connector *Weight 6,4 Kg *Packing: (LxDxH) 293 x 250 x 353 mm *7,7 Kg

Code	Lens	Price	Price
03.LDB153S.FW10	*SPOT lens *10°	**1 632.00 лв.**	1 958.40 лв.
03.LDB153S.FW25	*MEDIUM FLOOD lens *27°	**1 632.00 лв.**	1 958.40 лв.
03.LDB153S.FW40	*WIDE lens *40°	**1 632.00 лв.**	1 958.40 лв.


RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***176.00 лв.***	211.20 лв.

*KIT LENSES



Code	Description	Lens	Price	Price
03.LK.035	**Kit Lens for:** *TITAN SOLO FC (Full Colour RGBW) *TITAN SOLO CT (Full White)	*SPOT 8°	**169.60 лв.**	203.52 лв.
03.LK.036		*MEDIUM 20°	**131.20 лв.**	157.44 лв.
03.LK.037		*WIDE 36°	**131.20 лв.**	157.44 лв.

*BARNDOOR



Code	Description	Price	Price
03.LA.056.V1	Barndoor for TITAN V1 + Frame *GREY GLITTER	**124.80 лв.**	149.76 лв.
03.LA.096	Darklight louver for TITAN 54 and 48 Leds *Anti-Dazzling effect *GREY GLITTER	**92.80 лв.**	111.36 лв.

*CLAMPS / SAFETY WIRE



Code	Description	Price	Price
0521A004	G60 "C" Clamp (Max. load 50 Kg) *For Ø50mm tubes *Black recommended for *TITAN SOLO	**15.00 лв.**	18.00 лв.
0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black recommended for *TITAN SOLO	**13.76 лв.**	16.51 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

LED PROJECTORS

with power supply on board

ENTERTAINMENT

PAR 36 LED *SOLO

*IP20 (for Indoor installations)





!!! UNTIL SUPPLY LASTS !!!

Code	Description	Lens	Price	Price
03.P360201N0201	**PAR 36 LED *SOLO *WARM WHITE *black**	*SPOT lens *10°	**326.40 лв.**	391.68 лв.
03.P360201M0201	*9 LEDs Lamp AR 111 *Warm White 3.200 K *x.xxx Lux / 2 m *Life:75.000 h *No infrared / ultraviolet emission *3 lenses set available (Spot, Medium flood, Wide flood) *Power Supply 500mA on Board * 100-240 V*Dimming ON-OFF Only *Aluminium thickness: 20/10 *High quality aluminium: 99,5% *Rounded front border of the body for more strength *Bracket with 0° ÷ 90° rotation *Connection: *3x0,75 sq.mm cable *0,85 mt *Schuko plug *Weight: 1,1 Kg *Packing (LxDxH) 590x460x245 mm *xx	*MEDIUM FLOOD lens *25°	**326.40 лв.**	391.68 лв.
03.P360201W0201		*WIDE lens *40°	**326.40 лв.**	391.68 лв.
03.P360201N0202	**PAR 36 LED *SOLO *NATURAL WHITE *black**	*SPOT lens *10°	**326.40 лв.**	391.68 лв.
03.P360201M0202	*Same as above but with *9 LEDs Lamp AR 111 *Natural White 4.500 K *x.xxx Lux / 2 m	*MEDIUM FLOOD lens *25°	**326.40 лв.**	391.68 лв.
03.P360201W0202		*WIDE lens *40°	**326.40 лв.**	391.68 лв.
03.P360201N0202	**PAR 36 LED *SOLO *COLD WHITE *black**	*SPOT lens *10°	**326.40 лв.**	391.68 лв.
03.P360201M0202	*Same as above but with *9 LEDs Lamp AR 111 *Cold White 6.000 K *x.xxx Lux / 2 m	*MEDIUM FLOOD lens *25°	**326.40 лв.**	391.68 лв.
03.P360201W0202		*WIDE lens *40°	**326.40 лв.**	391.68 лв.

LED PROJECTORS

with Bracket

ENTERTAINMENT

PAR 36 LED

*IP20 (for Indoor installations)





!!! UNTIL SUPPLY LASTS !!!

Code	Description	Lens	Price	Price
03.P360201N0101	**PAR 36 LED *WARM WHITE *black**	*SPOT lens *10°	**268.80 лв.**	322.56 лв.
03.P360201M0101	*9 LEDs Lamp AR 111 *Warm White 3.200 K *x.xxx Lux / 2 m *Life:75.000 h *No infrared / ultraviolet emission *3 lenses set available (Spot, Medium flood, Wide flood) *Power Supply not Included (Z-series) *Variable dimming by DMX. *Aluminium thickness: 20/10 *High quality aluminium: 99,5% *Rounded front border of the body for more strength *Bracket with 0° ÷ 90° rotation *Connection: *3x0,75 sq.mm cable *0,85 mt *Schuko plug *Weight: 1,1 Kg *Packing (LxDxH) 590x460x245 mm *xx	*MEDIUM FLOOD lens *25°	**268.80 лв.**	322.56 лв.
03.P360201W0101		*WIDE lens *40°	**268.80 лв.**	322.56 лв.
03.P360201N0102	**PAR 36 LED *NATURAL WHITE *black**	*SPOT lens *10°	**268.80 лв.**	322.56 лв.
03.P360201M0102	*Same as above but with *9 LEDs Lamp AR 111 *Natural White 4.500 K *x.xxx Lux / 2 m	*MEDIUM FLOOD lens *25°	**268.80 лв.**	322.56 лв.
03.P360201W0102		*WIDE lens *40°	**268.80 лв.**	322.56 лв.
03.P360201N0103	**PAR 36 LED *COLD WHITE *black**	*SPOT lens *10°	**268.80 лв.**	322.56 лв.
03.P360201M0103	*Same as above but with *9 LEDs Lamp AR 111 *Cold White 6.000 K *x.xxx Lux / 2 m	*MEDIUM FLOOD lens *25°	**268.80 лв.**	322.56 лв.
03.P360201W0103		*WIDE lens *40°	**268.80 лв.**	322.56 лв.

*Accessories

PAR 36 LED


*KIT LENSES




Code	Description	Lens	Price	Price
0506A035	**Kit Lens for:**	*SPOT (10°)	**58.24 лв.**	69.89 лв.
0506A036	*PAR 36 LED *PAR 36 LED SOLO	*MEDIUM FLOOD (25°)	**58.24 лв.**	69.89 лв.
0506A037		*WIDE FLOOD (40°)	**58.24 лв.**	69.89 лв.

*POWER SUPPLY and DMX controller









Code	Description	Connection	Price	Price
03.LA.080.V2	Z8 INDOOR Rack *8 Groups *500mA / 48V *Screw terminals *PAR 36 LED *WHITE 3200K / 4500K / 6000K * Min **1** / Max **32** units connected (Max 4 pcs each group)	*Screw terminals	**2 288.00 лв.**	2 745.60 лв.
03.LA.075.V2	Z8 INDOOR Rack *8 Groups *500mA / 48V *M12 *PAR 36 LED *WHITE 3200K / 4500K / 6000K * Min **1** / Max **32** units connected (Max 4 pcs each group)	*M12	**2 288.00 лв.**	2 745.60 лв.
03.LA.009P	Z1 PLUS INDOOR *1 Group 500mA / 60V *RJ45/Plug-in *PAR 36 LED *WHITE 3200K / 4500K / 6000K * Min **1** / Max **5** units connected	*Screw terminals *RJ45	**640.00 лв.**	768.00 лв.

*CLAMPS / SAFETY WIRE



Code	Description	Price	Price
0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black recommended for *PAR 36 LED *PAR 36 LED SOLO	**13.76 лв.**	16.51 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

LED CONTROLLERS

ENTERTAINMENT

Z-Series



Image	Code	Product	Connection		Price	Price
	03.LA.080.V2	**Z8 INDOOR Rack** *8 Out *32 Ch *500mA / 48V *full-range AC 90-260 V, 50-60 Hz *Outputs: Nr. 8 *Channels: 32 Ch (4 Ch x 8 outputs) *M12 or SCREW TERMINALS (Plug-in) connection system or RJ45 (On demand) *Power: 96W x output (24W x 4 ch.) *Current VOUT: *500mA *48V *3 DMX modes *32 ch, 9 ch. or custom mode. *LCD graphic display *16 pre-programmed Color Macros *16 pre-programmed White Macros *1 Demo (rainbow) *1 Color Macro (user editable) *Control Via any DMX control *Internal Updatable operating system by RED BOX *Boost function selectable by user, let you increase by 40% the power of connected LEDs. *Master or Slave mode (max 32 Slave units for each Master) *IR remote control (optional) available *Emergency Function *IP20 protection level. *Housed in a sturdy metal case, that offers high resistance to knocks and mechanical stress *The case is covered with a coat of epoxy paint. *2U Rack mountable	*Screw terminals	Stripped cable	**2 288.00 лв.**	2 745.60 лв.
	03.LA.075.V2		*M12		**2 288.00 лв.**	2 745.60 лв.

Image	Code	Product	Connection		Price	Price
	03.LA.009P	**Z1 PLUS *IP20** *1 Out *4 Ch *500mA / 60V *full-range AC 90-260 V, 50-60 Hz *Outputs: Nr. 1 *Channels: 4 Ch (4 Ch x 1 output) *RJ45 / SCREW (Plug-in) connection system *Power: 100W (25W x 4 ch.) *Current VOUT: 500mA 60V *2 DMX modes *10 or ch 6 ch. *LED display *16 pre programmed Color Macros *16 pre-programmed White Macros *1 Demo (rainbow) *1 Color Macro (user editable) *Included items: 2U Rack Wing Adapter (x1) *RJ 45 Male (x2) *Control Via any DMX control *Internal Updatable operating system by RED BOX *Boost function selectable by user, let you increase by 30% the power of connected LEDs. *Master or Slave mode (max 32 Slave units for each Master) *IR remote control (optional) available *Emergency Function *IP20 protection level. *Housed in a sturdy metal case, that offers high resistance to knocks and mechanical stress *The case is covered with a coat of epoxy paint.	***IP20 (INDOOR)** *Screw terminals *RJ45	Stripped cable	**640.00 лв.**	768.00 лв.

BLINDERS

ENTERTAINMENT

FLASH

*IP20 (for Indoor installations)

Image	Code	Product	Price	Price
	03.E1173	**FLASH 2000 L (Linear) black** • LIGHT SOURCE: 2 PAR 36 650W 120V lamps (NOT INCLUDED) *Fix pairs • CONSUMPTION: 1.300W • VOLTAGE: 230V 50/60 Hz • WIRING: Ready-wired with silicone cables • PACKING: (LxDxH) 300 x 210 x 490 mm *3,3 Kg	**120.00 лв.**	144.00 лв.
	03.E1171	**FLASH 4000 L (Linear) black** • LIGHT SOURCE: 4 PAR 36 650W 120V lamps (NOT INCLUDED) *Fix • CONSUMPTION: 2.600W • VOLTAGE: 230V 50/60 Hz • WIRING: Ready-wired with silicone cables • PACKING: (LxDxH) 310 x 220 x 680 mm *4,5 Kg	**200.00 лв.**	240.00 лв.
	03.E1170	**FLASH 4000 (Square) black** • LIGHT SOURCE: 4 PAR 36 650W 120V lamps (NOT INCLUDED) *Fix • CONSUMPTION: 2.600W • VOLTAGE: 230V 50/60 Hz • WIRING: Ready-wired with silicone cables • PACKING: (LxDxH) 470 x 260 x 580 mm *5,9 Kg	**190.00 лв.**	228.00 лв.

*Accessories

BLINDERS

*CLAMPS / SAFETY WIRE



Code	Description	Price	Price
0521A004	G60 "C" Clamp (Max. load 50 Kg) *For Ø50mm tubes *Black recommended for *FLASH	**15.00 лв.**	18.00 лв.
0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black recommended for *FLASH	**13.76 лв.**	16.51 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

WIRELESS DMX Transmitter and Receivers

ANTENNA FLEX *IP20 (for Indoor installations)



03.E12100

ANTENNA DMX FLEX *IP20 *Transmitter / Receiver

ANTENNA is a wireless DMX system which employs the W-DMX technology. ANTENNA is compact, easy to install and simple to use.
• WIRELESS TECH: *Adaptive FHSS (Frequency Hopping Spread Spectrum). *83 working channels in various broadcasting frequency (without any interference) *Ideal for trasmissions Multi-cast e Point-to-point. • DATA TX/RX: *512 DMX channels • IP20 protection rated • POWER SUPPLY: *Input: 90V AC – 250V AC 50-60 Hz *Max: 1A at 115V AC – 0,5A at 230V AC • COMPLIANCE: *In Conformity to international Security standards: *ETSI: EN300 328 & 300 826,*EMC: EN301 489-17, *CE: EN60950, *FCC: Part 15 Sec. 247 & Subpart B • INCLUDED ITEMS: *2dBi IP20 Omnidirectional antenna (HxV) 360°x360° *Range 500 mt. • PACKING: (LxDxH) 170 x 180 x 100 mm *1,5 Kg

704.00 лв. 844.80 лв.

***Spare ANTENNA**



Code	Description	Price	Price
0508A033	2-dBi ANTENNA Omini-directional IP20 INDOOR *Omni-directional, radiation (HxV) 360°x360°. Distance: 500mt approx	**15.04 лв.**	18.05 лв.
0508A048	5-dBi ANTENNA Omini-directional IP20 INDOOR *Omni-directional, radiation (HxV) 360°x90°. Distance: 1000mt approx	**53.76 лв.**	64.51 лв.
0508A049	7-dBi ANTENNA Omini-directional IP20 INDOOR *Omni-directional, radiation (HxV) 360°x20°. Distance: 1500mt approx	**89.60 лв.**	107.52 лв.

***CABLE ADAPTER**



Code	Description	Price	Price
0508A042	Interface adaptor from OUTDOOR CABLE to INDOOR DBI ANTENNA range	**20.48 лв.**	24.58 лв.

ANTENNA FLEX *IP65 (for Outdoor installations)



03.E12101

ANTENNA DMX FLEX IP65 *Transmitter / Receiver

ANTENNA is a wireless DMX system which employs the W-DMX technology. ANTENNA is compact, easy to install and simple to use.
• WIRELESS TECH: *Adaptive FHSS (Frequency Hopping Spread Spectrum). *83 working channels in various broadcasting frequency (without any interference) *Ideal for trasmissions Multi-cast e Point-to-point. • DATA TX/RX: *512 DMX channels • IP65 protection rated • POWER SUPPLY: *Input: 90V AC – 250V AC 50-60 Hz *Max: 1A at 115V AC – 0,5A at 230V AC • COMPLIANCE: *In Conformity to international Security standards: *ETSI: EN300 328 & 300 826,*EMC: EN301 489-17, *CE: EN60950, *FCC: Part 15 Sec. 247 & Subpart B • INCLUDED ITEMS: *2dBi IP65 Omnidirectional antenna (HxV) 360°x360° *Range 500 mt. • PACKING: (LxDxH) 366 x 262 x 84 mm *1,5 Kg

992.00 лв. 1 190.40 лв.

***Spare ANTENNA**



Code	Description	Price	Price
0508A040	2-dBi ANTENNA Omini-directional IP65 OUTDOOR *Omni-directional, radiation (HxV) 360°x360°. Distance: 500mt approx	**118.40 лв.**	142.08 лв.
0508A043	5-dBi ANTENNA Omini-directional IP65 OUTDOOR *Omni-directional, radiation (HxV) 360°x30°. Distance: 1000mt approx	**134.40 лв.**	161.28 лв.
0508A044	8-dBi ANTENNA Omni-directional IP65 OUTDOOR *Omni-directional, radiation (HxV) 360°x20°. Distance: 1800mt approx	**179.20 лв.**	215.04 лв.

***CABLE ADAPTER**



Code	Description	Price	Price
0508A042	Interface adaptor from OUTDOOR CABLE to INDOOR DBI ANTENNA range	**20.48 лв.**	24.58 лв.

DMX CONTROLERS

ENTERTAINMENT

MASTER SOFTWARE 2





03.E1260

MASTER SOFTWARE 2 *DMX Controller Interface

DMX MASTER SOFTWARE 2 is a DMX light control software for PC, supplied bundled with the DMX 512 IN / OUT interface.
Easy to program thanks to rich graphic interface. Convenient for all kinds of performances; the easiest software **(New Version V.3)** for show programming.
• CONTROL: *Management of lighting groups and fixtures functions
• PROGRAMABILITY: *Automatic change of lightings address *Unlimited scenes, programs, steps, series, sequences and effects
*Virtual scenes; Scenes generator *Big fixtures internal library *Musical synchronization available (BPM, MP3, WAV and Audio In)
*Compatible with all DMX projectors *Compatible USB 1 and 2 *512 DMX channels out / 264 DMX channels out in Stand alone mode
*Internal storage and 2 buttons to chose scenes in Stand alone mode.
* Connection HE10, to play scenes and effects using a external controller *The software can control up to 6 Box interfaces contemporarely.
• PACKING: (LxDxH) 190x250x60 mm *0,5 Kg

864.00 лв. 1 036.80 лв.

***Power Supply**



Code	Description	Price	Price
0508T015	Stabilized PSU 5VDC MINI USB for MASTERSOFTWARE 2	**24.00 лв.**	28.80 лв.

DIMMERS

ENTERTAINMENT

DPU 1213

	Code	Product	Price	Price
	03.DC006	**DPU 1213 black *3-phase 380V 50Hz *12 Ch *13A *Cabur** *Professional dimmers controllable either manually or via DMX. *12-channel dimmer pack for resistance or induction loads *Max current output: 13A per channel* Channels controlled via DMX *Channels protected by magneto thermic circuit breakers *Internal microprocessor with functions menu *Functions displayed on LCD display *Choice of different EQ curves for each channel *Setting of pre-heating for each channel *Power supply: 3-phase 380V 50Hz *Output: CABUR connectors *Dimensions 3U rack units *Weight 11 Kg *Packing (LxDxH) 530 x 470 x 120 mm *12,5 Kg	**2 608.00 лв.**	3 129.60 лв.

DPU 613

	Code	Product	Price	Price
	03.DC007	**DPU 613 black *3-phase 380V 50Hz *6 Ch *13A *Cabur** *Professional dimmers controllable either manually or via DMX. *6-channel dimmer pack for resistance or induction loads *Max current output: 13A per channel* Channels controlled via DMX *Channels protected by magneto thermic circuit breakers *Internal microprocessor with functions menu *Functions displayed on LCD display *Choice of different EQ curves for each channel *Setting of pre-heating for each channel *Power supply: 3-phase 380V 50Hz *Output: CABUR connectors *Dimensions 3U rack units *Weight 4,5 Kg *Packing (LxDxH) 530 x 470 x 120 mm *5,1 Kg	**1 728.00 лв.**	2 073.60 лв.

*Connectors

	Code	Product	Price	Price
	02K00524	ILME MALE CONNECTOR CNM1 for DP Dimmers *1 pcs for DPU 613 H	**48.00 лв.**	57.60 лв.

SPLITTERS

ENTERTAINMENT

SPLITTER 6-CH

	Code	Product	Price	Price
	0521S016	**SPLITTER 6-CH *6 Out** • OVERVIEW: Distributor / Amplifier of DMX Signals • CONTROL: *1 DMX In / 6 DMX Out *DMX inputs and outputs with 5-pole XRL connectors by Neutrik • SAFETY: *Opto-isolated DMX channels *230V • DISPLAY: LCD Display for monitoring all functions and settings. • DIMENSIONS: 1U Rack mountable *2,3 Kg • PACKING: (LxDxH) 560 x 280 x 120 mm *3,4 Kg	**640.00 лв.**	768.00 лв.
	0521S030	**SPLITTER 6-CH *PRO *6 Out** • OVERVIEW: Distributor / Amplifier of DMX Signals • CONTROL: *1 DMX In / 6 DMX Out *DMX inputs and outputs with 5-pole XRL connectors by Neutrik • SAFETY: ***Opto-isolated and galvanically-isolated DMX channels** *230V • DISPLAY: LCD Display for monitoring all functions and settings. • DIMENSIONS: 1U Rack mountable *2,3 Kg • PACKING: (LxDxH) 560 x 280 x 120 mm *3,4 Kg	**1 200.00 лв.**	1 440.00 лв.

THEATER LED Projectors

ENTERTAINMENT

SCENA LED

*IP20 (for Indoor installations)



SCENA 150 LED *PC (Antihalo) *black

*SCENA LED is a compact, lightweight, DMX-controlled LED projector featuring a single high-power White LED and a long excursionlinear motorized zoom with high-efficiency optical system. The unit is wireless ready. SCENA LED is a modern alternative to conventional lights, improving light quality, flexibility of use and installation, energy savings and component duration. The fixture doesn't heat up, and the projection is always flicker free. The dimming curves are similar to those of halogen lamps. • LED TECHNOLOGY: 1 x White LED (3.000 °K) CRI>90; (4.000 °K and 5.600 °K LEDs also available)
• OPTICAL GROUP: Ø 120 mm PC lens, 3.565 Lux / 3 m *8,8° - 74° linear motorized zoom
• CONTROL: *4 DMX channels *LED display + 4 soft keys *Wireless ready • CONNECTORS: *Powercon In & Out *5-poles DMX In & Out • POWER SUPPLY: Electronic full-range AC 90-260 V 50 / 60 Hz
*WEIGHT: 5,35 Kg *Packing (LxDxH) 300 x 235 x 425 mm *6,25 Kg

Code	Version	Price	Price
03.TS016.A	*WHITE 3.000 K	1 478.40 лв.	1 774.08 лв.
03.TS017.A	*WHITE 4.000 K	1 478.40 лв.	1 774.08 лв.
03.TS018.A	*WHITE 5.600 K	1 478.40 лв.	1 774.08 лв.



SCENA 150 LED *FR (Fresnel) *black

*SCENA LED is a compact, lightweight, DMX-controlled LED projector featuring a single high-power White LED and a long excursionlinear motorized zoom with high-efficiency optical system. The unit is wireless ready. SCENA LED is a modern alternative to conventional lights, improving light quality, flexibility of use and installation, energy savings and component duration. The fixture doesn't heat up, and the projection is always flicker free. The dimming curves are similar to those of halogen lamps. • LED TECHNOLOGY: 1 x White LED (3.000 °K) CRI>90; (4.000 °K and 5.600 °K LEDs also available)
• OPTICAL GROUP: Ø 120 mm Fresnel lens, 2.243 Lux / 3 m *12,7° - 65° linear motorized zoom
• CONTROL: *4 DMX channels *LED display + 4 soft keys *Wireless ready • CONNECTORS: *Powercon In & Out *5-poles DMX In & Out • POWER SUPPLY: Electronic full-range AC 90-260 V 50 / 60 Hz
*WEIGHT: 5,10 Kg *Packing (LxDxH) 300 x 235 x 425 mm *6,00 Kg

Code	Version	Price	Price
03.TS016.F	*WHITE 3.000 K	1 478.40 лв.	1 774.08 лв.
03.TS017.F	*WHITE 4.000 K	1 478.40 лв.	1 774.08 лв.
03.TS018.F	*WHITE 5.600 K	1 478.40 лв.	1 774.08 лв.

	Option	Description	Price	Price
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***48.00 лв.***	57.60 лв.
	.WS option	*Assembled with Wireless Board + 2 Dbi IP65 Antenna on board **(Extra Cost)***	***240.00 лв.***	288.00 лв.

SCENA LED MN (Manual)

*IP20 (for Indoor installations)



!!! NEW !!!

SCENA 150 LED *MN *PC (Antihalo) *black

*SCENA LED is a compact, lightweight, LED projector featuring a single high-power White LED and a long excursion linear manual zoom with high-efficiency optical system. SCENA LED is a modern alternative to conventional lights, improving light quality, flexibility of use and installation, energy savings and component duration. The fixture doesn't heat up, and the projection is always flicker free. The dimming curves are similar to those of halogen lamps.*LED TECHNOLOGY: 1 x White LED (3.000 °K) CRI>90; (4.000 °K and 5.600 °K LEDs also available) *OPTICAL GROUP: Ø 120 mm PC lens, 3.565 Lux / 3 m *8,8° - 74° manual zoom *CONTROL: MANUAL Zoom via Knobs; MANUAL Dim via Knobs *CONNECTORS: Powercon In & Out *POWER SUPPLY: Electronic full-range AC 90-260 V 50 / 60 Hz *WEIGHT: 5,35 Kg *Packing (LxDxH) 300 x 235 x 425 mm *6,25 Kg

Code	Version	Price	Price
03.TS019.A	*WHITE 3.000 K	992.00 лв.	1 190.40 лв.
03.TS020.A	*WHITE 4.000 K	992.00 лв.	1 190.40 лв.
03.TS021.A	*WHITE 5.600 K	992.00 лв.	1 190.40 лв.



!!! NEW !!!

SCENA 150 LED *MN *FR (Fresnel) *black

*SCENA LED is a compact, lightweight, LED projector featuring a single high-power White LED and a long excursion linear manual zoom with high-efficiency optical system. SCENA LED is a modern alternative to conventional lights, improving light quality, flexibility of use and installation, energy savings and component duration. The fixture doesn't heat up, and the projection is always flicker free. The dimming curves are similar to those of halogen lamps.*LED TECHNOLOGY: 1 x White LED (3.000 °K) CRI>90; (4.000 °K and 5.600 °K LEDs also available) *OPTICAL GROUP: Ø 120 mm Fresnel lens, 2.243 Lux / 3 m * 12,7° - 65° manual zoom *CONTROL: MANUAL Zoom via Knobs; MANUAL Dim via Knobs *CONNECTORS: Powercon In & Out *POWER SUPPLY: Electronic full-range AC 90-260 V 50 / 60 Hz *WEIGHT: 5,10 Kg *Packing (LxDxH) 300 x 235 x 425 mm *6,00 Kg


Code	Version	Price	Price
03.TS019.F	*WHITE 3.000 K	992.00 лв.	1 190.40 лв.
03.TS020.F	*WHITE 4.000 K	992.00 лв.	1 190.40 лв.
03.TS021.F	*WHITE 5.600 K	992.00 лв.	1 190.40 лв.

	Option	Description	Price	Price
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***48.00 лв.***	57.60 лв.

*Accessories

SCENA LED

*BARNDOOR



Code	Description	Price	Price
03.TBD01	Barndoor for SCENA 150 LED *Black finishing	**44.80 лв.**	53.76 лв.
.03 WHITE option	White finishing **(Extra Cost)**	**22.40 лв.**	26.88 лв.

*LENSES



Code	Description	Price	Price
0506P004	Lens for SCENA 150 LED FRESNEL *Ø 120mm	**35.20 лв.**	42.24 лв.
0506P003	Lens for SCENA 150 LED PC/ANTIHALO *Ø 120mm	**43.84 лв.**	52.61 лв.

*CLAMPS / SAFETY WIRE



Code	Description	Price	Price
0521A004	G60 "C" Clamp (Max. load 50 Kg) *For Ø50mm tubes *Black recommended for *SCENA LED	**15.00 лв.**	18.00 лв.
0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black recommended for *SCENA LED	**13.76 лв.**	16.51 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

SCENA S

*IP20 (for Indoor installations)



SCENA S 2000 black

*New optical group with custom-built lenses, PC or Fresnel *Over 30% extra luminosity *Extremely smooth and precise lamp holder movement on a triple track *Wider max beam aperture angle. *LAMP NOT INCLUDED • SAFETY: *new protective grill mesh *yoke with a new round flange + clutch system which guarantees a perfect grip and safer operation *new front and rear safety hooks *Stronger housing with new folded edges, designed to resist all the rigours of continuous use. • Theatre light for 2000W lamps with Socket GY16 • POWER SUPPLY: *230V 50/60Hz *Power cable length: 1 m *Strain relief cable clamp • WEIGHT: *7,5 Kg *Packing (LxDxH)390 x 510 x 300 mm *9 Kg (1 units each box)

Code	Version	Price	Price
03.TS013.F	*FR *Fresnel *Focal Adjustment: 10° to 55°	390.00 лв.	468.00 лв.
03.TS013.A	*PC *Antihalo *Focal Adjustment: 9° to 50°	415.00 лв.	498.00 лв.



SCENA S 1200 black

*New optical group with custom-built lenses, PC or Fresnel *Over 30% extra luminosity *Extremely smooth and precise lamp holder movement on a triple track *Wider max beam aperture angle. *LAMP NOT INCLUDED • SAFETY: *new protective grill mesh *yoke with a new round flange + clutch system which guarantees a perfect grip and safer operation *new front and rear safety hooks *Stronger housing with new folded edges, designed to resist all the rigours of continuous use. • Theatre light for 1200W lamps with Socket GX9,5 • POWER SUPPLY: *230V 50/60Hz *Power cable length: 1 m *Strain relief cable clamp • WEIGHT: *x Kg *Packing (LxDxH) 610 x 440 x 250 mm *x Kg (x units each box)

Code	Version	Price	Price
03.TS014.F	*FR *Fresnel *Focal Adjustment: 10° to 60°	320.00 лв.	384.00 лв.
03.TS014.A	*PC *Antihalo *Focal Adjustment: 9° to 58°	288.00 лв.	345.60 лв.



SCENA S 750 black

*New optical group with custom-built lenses, PC or Fresnel *Over 30% extra luminosity *Extremely smooth and precise lamp holder movement on a triple track *Wider max beam aperture angle. *LAMP NOT INCLUDED • SAFETY: *new protective grill mesh *yoke with a new round flange + clutch system which guarantees a perfect grip and safer operation *new front and rear safety hooks *Stronger housing with new folded edges, designed to resist all the rigours of continuous use. • Theatre light for 750W HPL lamps with HPL Socket • POWER SUPPLY: *230V 50/60Hz *Power cable length: 1 m *Strain relief cable clamp • WEIGHT: *x Kg *Packing (LxDxH) 610 x 440 x 250 mm *x Kg (x units each box)

Code	Version	Price	Price
03.TS015.F	*FR *Fresnel *Focal Adjustment: x° to x°	320.00 лв.	384.00 лв.
03.TS015.A	*PC *Antihalo *Focal Adjustment: x° to x°	288.00 лв.	345.60 лв.



SCENA S 650/1000 black

*New optical group with custom-built lenses, PC, Fresnel or Optical *Over 30% extra luminosity *Extremely smooth and precise lamp holder movement on a triple track *Wider max beam aperture angle. *LAMP NOT INCLUDED • SAFETY: *new protective grill mesh *yoke with a new round flange + clutch system which guarantees a perfect grip and safer operation *new front and rear safety hooks *Stronger housing with new folded edges, designed to resist all the rigours of continuous use. *Teatre light for 650W or 1000W lamps with Socket GX9,5 • POWER SUPPLY: *230V 50/60Hz *Power cable length: 1 m *Strain relief cable clamp • WEIGHT: *4 Kg *Packing (LxDxH) 610 x 440 x 250 mm 11 Kg (2 units each box)

Code	Version	Price	Price
03.TS012.F	*FR *Fresnel *Focal Adjustment: 12° to 53°	235.00 лв.	282.00 лв.
03.TS012.A	*PC *Antihalo *Focal Adjustment: 10° to 64°	250.00 лв.	300.00 лв.
03.TS012.O	*OPT *Optical *Focal Adjustment: 13° to 56°	320.00 лв.	384.00 лв.



SCENA S 300/500 black

*New optical group with custom-built lenses, PC or Fresnel *Over 30% extra luminosity *Extremely smooth and precise lamp holder movement on a triple track *Wider max beam aperture angle. *LAMP NOT INCLUDED • SAFETY: *new protective grill mesh *yoke with a new round flange + clutch system which guarantees a perfect grip and safer operation *new front and rear safety hooks *Stronger housing with new folded edges, designed to resist all the rigours of continuous use. • Theatre light for 300W or 500W lamps with Socket GY9,5 • POWER SUPPLY: *230V 50/60Hz *Power cable length: 1 m *Strain relief cable clamp • WEIGHT: *3 Kg *Packing (LxDxH) (LxDxH) 510 x 400 x 430 mm 16 Kg (4 units each box)

Code	Version	Price	Price
03.TS011.F	*FR *Fresnel *Focal Adjustment: 12° to 53°	220.00 лв.	264.00 лв.
03.TS011.A	*PC *Antihalo *Focal Adjustment: 10° to 64°	220.00 лв.	264.00 лв.

RAL 9003	Code	Description	Price	Price
RAL 9003	**.03 WHITE** option	*White finishing **(Extra Cost)***	***48.00 лв.***	57.60 лв.

*BARNDOOR



Code	Description	Price	Price
03.TBD03	Barndoor for SCENA 2000 *Black finishing	**60.00 лв.**	72.00 лв.
03.TBD02	Barndoor for SCENA 650/1000 *Black finishing	**50.00 лв.**	60.00 лв.
03.TBD01	Barndoor for SCENA 300/500 *Black finishing	**45.00 лв.**	54.00 лв.
.03 WHITE option	White finishing **(Extra Cost)**	**22.40 лв.**	26.88 лв.

*LENSES





Code	Description	Price	Price
0506P009	Lens for SCENA 2000 FRESNEL *Ø 200mm	**60.00 лв.**	72.00 лв.
0506P008	Lens for SCENA 2000 PC/ANTIHALO *Ø 200mm	**110.00 лв.**	131.00 лв.
0506P015	Lens for SCENA 650/1000 FRESNEL *Ø 150mm	**35.00 лв.**	42.00 лв.
0506P006	Lens for SCENA 650/1000 OPTICAL *Ø 150mm	**130.24 лв.**	156.29 лв.
0506P005	Lens for SCENA 650/1000 PC/ANTIHALO *Ø 150mm	**55.00 лв.**	66.00 лв.
0506P004	Lens for SCENA 300/500 FRESNEL *Ø 120mm	**40.00 лв.**	48.00 лв.
0506P003	Lens for SCENA 300/500 PC/ANTIHALO *Ø 120mm	**45.00 лв.**	54.00 лв.

*CLAMPS / SAFETY WIRE



Code	Description	Price	Price
0521A004	G60 "C" Clamp (Max. load 50 Kg) *For Ø50mm tubes *Black recommended for *SCENA S	**15.00 лв.**	18.00 лв.
0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black recommended for *SCENA S	**13.76 лв.**	16.51 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

THEATER Cyclorama

ENTERTAINMENT

CYCLO 1000

*IP20 (for Indoor installations)



Code	Product	Version	Price	Price
03.CL001	**CYCLO 1000 black** CYCLO 1000 is a compact and lightweight projector for 1.000W lamps designed for lightin g and colouring large cycloramas with a homogeneous projection. *R7S lamp holder for 1.000 W lamps *LAMP NOT INCLUDED *Extremely strong housing made from high-quality aluminium and stainless steel *Frontal safety glass *Reversible colour filter cassette *Efficient internal ventilation labyrint *Reinforced reversible bracket *Easy opening for re-lamping and cleaning *Internal safety microswitch *230V 50/60 Hz • WEIGHT: 5,1 Kg *Packing (LxDxH) 660 x 440 x 250 mm *6 Kg	***ASY *Asymmetrical Reflector** (810 Lux / 5 mt)	**428.80 лв.**	514.56 лв.
03.CL002		***SYM *Symmetrical Reflector** (790 Lux / 5 mt)	**428.80 лв.**	514.56 лв.

*Accessories

CYCLO

***BRACKETS**



Code	Description	Price	Price
02SK0077	Kit Brackets to interconnect multiple units of CYCLO 1000 *SQUARE: * up to 2 x 2 cyclo *LINEAR: No limit	**32.64 лв.**	39.17 лв.

***CLAMPS / SAFETY WIRE**



Code	Description	Price	Price
0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black recommended for *CYCLO	**13.76 лв.**	16.51 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

THEATER LED Shaper

ENTERTAINMENT

PROFILO LED

*IP20 (for Indoor installations)




Code	Product	Version	Price	Price
03.TP012	**PROFILO LED 150 black** PROFILO LED 150 is a professional shaper featuring a single high-power White LED. 1 x White LED (3.000K) CRI>90; (4.000K and 5.600K LEDs available) • OPTICAL GROUP: *1.800 Lux / 5 m *13,5°- 30° linear zoom with high-efficiency optical system • SHUTTERS: Internal rotating system with four removable shutters • CONTROL: 4 DMX channels; LED display + 4 soft keys; Wireless ready • CONNECTORS: Powerconn In & Out; 5-pole DMX In & Out • POWER SUPPLY: Electronic full-range AC 90-260 V 50/60 Hz	***WHITE 3.000 K**	**1 936.00 лв.**	2 323.20 лв.

*Accessories

PROFILO LED

***GOBOHOLDER & IRIS / DIAGPHRAM**



Code	Description	Price	Price
03.TA202	Gobo holder for PROFILO LED *Type B *Gobo size: 86mm (external), 60mm (figure)	**20.00 лв.**	24.00 лв.
03.TA201	Iris Diaphragm for PROFILO LED	**100.00 лв.**	120.00 лв.

***CLAMPS / SAFETY WIRE**



Code	Description	Price	Price
0521A004	G60 "C" Clamp (Max. load 50 Kg) *Black recommended for *SCENA S	**15.00 лв.**	18.00 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

PROFILO *IP20 (for Indoor installations)

PROFILO 1200 black



Code	Description	Features	Price	Price incl. VAT
03.TP010	*High definition zoom lens with double optical condenser lens *Optical tempered glass lenses with anti-reflective coating *Spherical reflector in polished and treated 99.9% aluminium *GX9,5 lampholder for 1200W lamps *LAMP NOT INCLUDED *Internal rotating system with four removable shutters. Shutters are mounted between plates with anti-abrasive surface *Zoom; Precision movement on a double track *Scales on zoom guides *Gobo holder type B for image projection (optional) *Gobo size: 86mm (external), 60mm (figure) *Iris diaphragm (optional) *Extremely compact and lightweight steel housing with aluminium edge profiles *Boxed gel holder (with total elimination of parasite light) *Internal ventilation labyrinth *Removable cover for easy access to lamp *Reversible yoke for using the projector in any position *Frontal protection grille (removable) *Heat insulated knobs and handles *Safety micro switches *Power supply 230V 50/60Hz *Packing (LxDxH) 800x350x350 mm 16 Kg	*Focal adjustment from 18° to 36° *GX9,5 lamp 1200W	**1 025.00 лв.**	1 230.00 лв.

PROFILO 1000 black



*High definition zoom lens with double optical condenser lens *Optical tempered glass lenses with anti-reflective coating *Spherical reflector in polished and treated 99.9% aluminium *GX9,5 lampholder for 1000W lamps *LAMP NOT INCLUDED *Internal rotating system with four removable shutters. Shutters are mounted between plates with anti-abrasive surface *Zoom; Precision movement on a double track *Scales on zoom guides *Gobo holder type B for image projection (optional) *Gobo size: 86mm (external), 60mm (figure) *Iris diaphragm (optional) *Extremely compact and lightweight steel housing with aluminium edge profiles *Boxed gel holder (with total elimination of parasite light) *Internal ventilation labyrinth *Removable cover for easy access to lamp *Reversible yoke for using the projector in any position *Frontal protection grille (removable) *Heat insulated knobs and handles *Safety micro switches *Power supply 230V 50/60Hz *Packing (LxDxH) 800x350x350 mm 16 Kg

Code	Features	Price	Price incl. VAT
03.TP001	*Focal adjustment from 18° to 36° *GX9,5 lamp 1000W	**975.00 лв.**	1 170.00 лв.
03.TP008	*Focal adjustment from 20° to 50° *GX9,5 lamp 1000W	**975.00 лв.**	1 170.00 лв.

PROFILO 750 black



Code	Description	Features	Price	Price incl. VAT
03.TP011	*High definition zoom lens with double optical condenser lens *Optical tempered glass lenses with anti-reflective coating *Spherical reflector in polished and treated 99.9% aluminium *lampholder for 750W HPL lamps *LAMP NOT INCLUDED *Internal rotating system with four removable shutters. Shutters are mounted between plates with anti-abrasive surface *Zoom; Precision movement on a double track *Scales on zoom guides *Gobo holder type B for image projection (optional) *Gobo size: 86mm (external), 60mm (figure) *Iris diaphragm (optional) *Extremely compact and lightweight steel housing with aluminium edge profiles *Boxed gel holder (with total elimination of parasite light) *Internal ventilation labyrinth *Removable cover for easy access to lamp *Reversible yoke for using the projector in any position *Frontal protection grille (removable) *Heat insulated knobs and handles *Safety micro switches *Power supply 230V 50/60Hz *Packing (LxDxH) 800x350x350 mm 16 Kg	*Focal adjustment from 30° to 55° *HPL lamp 750W	**1 024.00 лв.**	1 228.80 лв.


PROFILO 500 black



Code	Description	Features	Price	Price incl. VAT
03.TP002	*High definition zoom lens with double optical condenser lens *Optical tempered glass lenses with anti-reflective coating *Spherical reflector in polished and treated 99.9% aluminium *GY9,5 lampholder for 500W lamps *LAMP NOT INCLUDED *Internal rotating system with four removable shutters. Shutters are mounted between plates with anti-abrasive surface *Zoom; Precision movement on a double track *Scales on zoom guides *Gobo holder type B for image projection (optional) *Gobo size: 86mm (external), 60mm (figure) *Iris diaphragm (optional) *Extremely compact and lightweight steel housing with aluminium edge profiles *Boxed gel holder (with total elimination of parasite light) *Internal ventilation labyrinth *Removable cover for easy access to lamp *Reversible yoke for using the projector in any position *Frontal protection grille (removable) *Heat insulated knobs and handles *Safety micro switches *Power supply 230V 50/60Hz *Packing (LxDxH) 557x287x245 mm 8 Kg	*Focal adjustment from 20° to 50° *GY9,5 lamp 500W	**704.00 лв.**	844.80 лв.

*Accessories PROFILO

*GOBOHOLDER & IRIS / DIAGPHRAM



Code	Description	Price	Price incl. VAT
03.TA202	Gobo holder for PROFILO *Type B *Gobo size: 86mm (external), 60mm (figure)	**20.00 лв.**	24.00 лв.
03.TA201	Iris Diaphragm for PROFILO	**100.00 лв.**	120.00 лв.

*CLAMPS / SAFETY WIRE



Code	Description	Price	Price incl. VAT
0521A004	G60 "C" Clamp (Max. load 50 Kg) *Black recommended for *PROFILO	**15.00 лв.**	18.00 лв.
0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.

PHARUS *IP20 (for Indoor installations) *Follow spots

Image	Code	Description	Version	Price	Price with VAT
	03.TP005.L	**PHARUS 1500 black** *Lamp: HTI 1500W/D7/600) INCLUDED *Lamp holder: SFc 10-4 with notch *New optical group with condenser lens *Zoom 7° ÷ 16° *Linear focus *Extractable iris-diaphragm *Mechanical dimmer with black-out *Colour changer (optional): 5 interchangeable gel filter holders *Automatic switching system between colours *Gobo holder for gobo projections (optional) *Made on aluminium and stainless steel *High resistance to heat and mechanical stress *Removable cover for easy access to lamp *Safety micro switches *External ballast (electromagnetic or electronic) 230V 50/60Hz *Power consumption 1600 VA, with built in power factor correction *Weight: 20,5 Kg (PHARUS); 17,9 Kg (electro-magnetic ballast); 6,8 Kg (electronic ballast) *Packing: (LxDxH) 1070x440x480 mm *45 Kg (MAGNETIC) *34 Kg (ELECTRONIC)	***MAGNETIC** *Zoom 7° - 16 *Magnetic Ballast 230 V	**2 950.00 лв.**	3 540.00 лв.
	03.TP005.EB.L		***ELECTRONIC** *Zoom 7° - 16 *Electronic Ballast 90-260 V	**4 320.00 лв.**	5 184.00 лв.
	03.TP009.L	**PHARUS 1200 black** *Lamp: HMI 1200S INCLUDED *Lamp holder: SFc 10-4 with notch *New optical group with condenser lens *Zoom 7° ÷ 16° *Linear focus *Extractable iris-diaphragm *Mechanical dimmer with black-out *Colour changer (optional): 5 interchangeable gel filter holders *Automatic switching system between colours *Gobo holder for gobo projections (optional) *Made on aluminium and stainless steel *High resistance to heat and mechanical stress *Removable cover for easy access to lamp *Safety micro switches *External ballast (electromagnetic or electronic) 230V 50/60Hz *Power consumption 1600 VA, with built in power factor correction *Weight: 20,5 Kg (PHARUS); 17,9 Kg (electro-magnetic ballast); 6,8 Kg (electronic ballast) *Packing: (LxDxH) 1070x440x480 mm *45 Kg (MAGNETIC) *34 Kg (ELECTRONIC)	***MAGNETIC** *Zoom 7° - 16 *Magnetic Ballast 230 V	**2 750.00 лв.**	3 300.00 лв.
	03.TP009.EB.L		***ELECTRONIC** *Zoom 7° - 16 *Electronic Ballast 90-260 V	**4 160.00 лв.**	4 992.00 лв.

MOON *IP20 (for Indoor installations) *Follow spots


Image	Code	Description	Version	Price	Price with VAT
	03.E0300.LAMP	**!!! UNTIL SUPPLY LASTS !!!** **MOON 1200 black** *Lamp: HMI 1200S lamp INCLUDED *Lamp holder *SFc 10-4 *Extractable diaphragm *Black-out *6 colors + white (3 dichroic filters) *Made on aluminium and stainless steel *High resistance to heat and mechanical stress *External electromagnetic ballast *Power consumption 1300 VA, with built-in factor correction *Packing (LxDxH) 890 x 440 x 400 mm; 34,5 Kg	***MAGNETIC** *Magnetic Ballast 230 V *1200W Discharge Lamp	**2 080.00 лв.**	2 496.00 лв.
	03.E0291.LAMP	**!!! UNTIL SUPPLY LASTS !!!** **MOON 575 black** *Lamp: HMI 575 lamp INCLUDED *Lamp holder *SFc 10-4 *Extractable diaphragm *Black-out *6 colors + white (3 dichroic filters) *Made on aluminium and stainless steel *High resistance to heat and mechanical stress *External electromagnetic ballast *Power consumption 600 VA, with built-in factor correction *Packing (LxDxH) 960 x 450 x 420 mm; 23,2 Kg	***MAGNETIC** *Magnetic Ballast 230 V *575W Discharge Lamp	**1 600.00 лв.**	1 920.00 лв.
	03.E0281.LAMP	**!!! UNTIL SUPPLY LASTS !!!** **MOON 1000 black** *Lamp: CP70 1000W halogen lamp INCLUDED *GX9,5 lamp holder *2 PC lenses *Extractable iris / diaphragm *Colour changer (optional) *Made on aluminium and stainless steel *High resistance to heat and mechanical stress *Power supply 220-240 V 50/60 Hz *Power consumption 1050 VA *Packing: (LxDxH) 860 x 440 x 400 mm; 14,5 Kg	***MAGNETIC** *Magnetic Ballast 230 V *1000W Halogen Lamp	**695.00 лв.**	834.00 лв.

*Accessories for FOLLOWSPOTS

*COLOURCHANGER

Image	Code	Description	Price	Price with VAT
	03.TA204	Colourchanger for PHARUS *5 Gels	**175.00 лв.**	210.00 лв.
	03.E0321	Colourchanger for MOON 1000	**100.00 лв.**	120.00 лв.

*GOBOHOLDER

Image	Code	Description	Price	Price with VAT
	03.TA205	Gobo holder for PHARUS *Type B *Gobo size: 86mm (external), 60mm (figure)	**25.00 лв.**	30.00 лв.

*TRIPOD

Image	Code	Description	Price	Price with VAT
	0521A007	Professional Tripod for PHARUS and MOON *Min / Max High: 90 cm / 140 cm *Closed Lenght: 105 cm *Footprint diam. 109 cm *Max Load 40 Kg *Weight: 6,5 Kg ***NEW** Professional spigot with aluminium handle ***NEW** improved blocking system	**240.00 лв.**	288.00 лв.
	TRIPOD-CASTORS	***NEW** Castors Kit for Professional Tripod for PHARUS and MOON **0521A007** *Composed by 3 castors easily mounted on Professional Tripod feet.	**125.00 лв.**	150.00 лв.

PAR *IP20 (for Indoor installations) *Parcans



Code	Product	Finishing	Price	Price
03.P64.10.01.00	**SUPERPAR 64** SUPERPAR 64 CLASSIC is a spotlight for PAR 64 lamp, specially designed for rental companies with classic form, with long body in two sections, with square filter frame. *Aluminium thickness: 25/10 *High quality aluminium: 99,5% *Thicker and larger clamp than standard PAR64. *Hinge holding front and rear part for easyer and faster relamping *Double clutch *Back ventilation hole with no grill for enabling the lamp adjustment. *Rounded front border of the body for more strength *Bracket with 0° ÷ 90° rotation *Filterframe radius-hooks for higher indeformability. *GX16 highest quality ceramic lampsocket with chromium plated contacts *With lamp rotation system for orientating the beam, Parsafe+external copper ground wire. *Lamp cable is screwed and not welded. *LAMP NOT INCLUDED *Lamp MAX 1.000 W *Complying the international norms EN 60598-1 and EN 60598-2-17) *Front protection grill with dense grid mesh. *Lampholding spring held by special calendering rolling *3x1,5 sq.mm silicone cable, 1,15 mt *GX16d lamp socket *cable gland *filterholder *lampholding spring. *Packing (LxDxH) 490 x 490 x 520mm; 12,5 Kg (4 pcs each box)	*BLACK Finishing	**90.00 лв.**	108.00 лв.





CLASSIC



CLASSIC PRO

Code	Product	Finishing	Price	Price
03.P64.06.01.00	**PAR 64 CLASSIC** *Aluminium thickness: 20/10 *High quality aluminium: 99,5% *Thicker and larger clamp than standard PAR64. *Rear ventilation hole with protection dense grid mesh. *Rounded front border of the body for more strength *Bracket with 0° ÷ 90° rotation *Filterframe radius-hooks for higher indeformability. *GX16 highest quality ceramic lampsocket with chromium plated contacts *Lamp cable is screwed and not welded. *LAMP NOT INCLUDED *Lamp MAX 1.000 W *Complying the international norms EN 60598-1 and EN 60598-2-17) *Front protection grill with dense grid mesh. *Lampholding spring held by special calendering rolling *Internal safety cable between rear and front parts *PAR 64 CLASSIC: Supplied with: silicone cable 3x1,5 sq mm , 1 mt with stripped ends *GX16d lamp socket, filterholder, lampholding spring. *Packing (LxDxH) 460 x 470 x 500 mm; 7,4 Kg (4 pcs each box)	*BLACK Finishing	**65.00 лв.**	78.00 лв.
03.P64.08.01.00	**PAR 64 CLASSIC PRO** Same as PAR 64 CLASSIC but: With lamp rotation system for orientating the beam *PARSAFE and external copper ground wire. *Back hole with no grill for enabling the rotation of the shell of lampholder. *Supplied with: silicone cable 3x1,5 sq mm , lenght 1,15 mt with stripped ends *GX16d lamp socket (fitted in a plastich shell), cable Gland, filterholder and lampholding spring. *Packing (LxDxH) 460 x 470 x 500 mm; 8,8 Kg (4 pcs each box)	*BLACK Finishing	**70.00 лв.**	84.00 лв.



Code	Product	Finishing	Price	Price
03.P56.02.01.00	**PAR 56 SHORT** *Aluminium thickness: 20/10 *High quality aluminium: 99,5% *Rounded front border of the body for more strength *Bracket with 0° ÷ 90° rotation *Filterframe radius-hooks for higher indeformability *GX16 highest quality ceramic lampsocket with chromium plated contacts *Lamp holder spring locked by roller blading *LAMP NOT INCLUDED *Lamp MAX 300 W *Complying the international norms EN 60598-1 and EN 60598-2-17) *Lampholding spring held by special calendering rolling *Silicone cable 3x1,5 sq mm , 1,15 mt with stripped ends, GX16d lamp socket ,filterholder and lampholding spring. *Packing (LxDxH) 420 x 630 x 850 mm; 12 Kg (12 pcs each box)	*BLACK Finishing	**40.00 лв.**	48.00 лв.



PAR 36 SHORT

The PAR 36 SHORT is a projector for PAR 36 lamp, with a 35W 6V transformer (50W 12V on demand), with single body.
*Aluminium thickness: 20/10 *High quality aluminium: 99,5%
*Rounded front border of the body for more strength *Bracket with 0° ÷ 90° rotation
*Fork terminals *Lamp holder spring locked by roller blading *Lampholder spring included.
*LAMP NOT INCLUDED
*MAX Lamp: 35W 6V / 50W 12V
*Complying the international norms EN 60598-1 and EN 60598-2-17)
*Wired with PVC cable3x0,75 sqmm, Length 0,65mt
*Packing (LxDxH) 390 x 520 x 220 mm; 16,30 Kg (12 pcs each box)

Code	Version	Price	Price
03.P36.02.01.35	*35W 6V *BLACK Finishing	**30.00 лв.**	36.00 лв.
03.P36.02.01.50	*50W 12V *BLACK Finishing	**35.00 лв.**	42.00 лв.

*KIT CABLES



Code	Description	*For	Price	Price
02K00102.1	Kit power supply PRO *3x1,5sq.mm cable *mt 1,15 *GX16d socket *Hi-temp. resistant plastic shell.	*SUPEPAR 64 *PAR 64 CLASSIC PRO	**20.00 лв.**	24.00 лв.
02K00103	Kit power supply STANDARD *3x1,0sq.mm cable *mt 1,50 *GX16d	*PAR 64 CLASSIC	**15.00 лв.**	18.00 лв.

*LAMP SOCKET



Code	Description	*For	Price	Price
0503E001	*GX16D Ceramic Lamp socket *Minimum order 10 pcs	*PAR 64 *PAR 56	**3.00 лв.**	3.60 лв.
0503G003	*GU/GZ10 Lamp socket for PAR 16 Line *Minimum order 10 pcs	*PAR 16	**0.83 лв.**	1.00 лв.
0503A003	*GX 5,3 Lamp socket for PAR 16 Line *Minimum order 10 pcs	*PAR 16	**0.96 лв.**	1.15 лв.


*KNOB



Code	Description	*For	Price	Price
02K00201	Knob for PAR 64, PAR 56, PAR 36 *Minimum order 10 pcs	*PAR 64 *PAR 56 *PAR 36	**1.00 лв.**	1.20 лв.
02K00207	Knob for PAR 20 *Minimum order 10 pcs	*PAR 20	**0.45 лв.**	0.54 лв.

*GENERAL ACCESSORIES

*CLAMPS

	0521A014	G-Quick clamp *(Max. load 80 Kg) with Fast-Lock system *recommended for *JACK *XR *NICK / F *DELTA 8 Line	**20.00 лв.**	24.00 лв.
	0521A015	G100 "C" Clamp *(Max. load 200 Kg) *Black *recommended for *JACK *XR *NICK *DELTA 8	**12.16 лв.**	14.59 лв.
	0521A008	ALISCAF clamp *(Max. load 100 Kg) *For tube 50 mm *recommended for *MAX	**39.36 лв.**	47.23 лв.
	0521A004	G60 "C" Clamp (Max. load 50 Kg) *For Ø50mm tubes *Black *recommended for *JACK *XR *NICK *DELTA 8 *FOS 100 SOLO *TITAN SOLO *FLASH *FOG	**15.00 лв.**	18.00 лв.
	0521A012	G50 "C" Clamp (Max. load 10 Kg) *For Ø50mm tubes *Black *recommended for *PAR 36 LED *FOS 100 SOLO *FLASH *FOG *SCENA * PROFILO	**13.76 лв.**	16.51 лв.
	0521A020	G30 "C" Clamp (Max. load 5 Kg) *For min Ø30mm / max Ø35mm tubes *Black *recommended for *PAR 20 *PAR 16 / 20 / 30 / 36 / 46 / 56 / 64	**10.24 лв.**	12.29 лв.
	0521A020.20	G30 "C" Clamp (Max. load 5 Kg) *For min Ø30mm / max Ø35mm tubes *Chrome *recommended for *PAR 20 *PAR 16 / 20 / 30 / 36 / 46 / 56 / 64	**10.56 лв.**	12.67 лв.
	02K00549	Omega Clamp *RAPTOR *MAX *WONDER with "Fast Lock" connection 1⁄4 turn ***Price for 1 pcs** *recommended for *RAPTOR *MAX *WONDER (2pcs needed)	**24.00 лв.**	28.80 лв.
	02K00523	Omega Clamp DELTA 12 with "Fast Lock" connection 1⁄4 turn ***Price for 1 pcs** *recommended for *DELTA 12 (2pcs needed)	**51.20 лв.**	61.44 лв.
	02K00467	Omega Clamp *XR JACK *NICK with "Fast Lock" connection 1⁄4 turn ***Price for 1 pcs** *recommended for *XR Moving heads *JACK *NICK NRG *NICK (1pcs needed)	**24.00 лв.**	28.80 лв.
	0521A010	Safety steel cable (3mm x 60 cm) *Ring spring catch *lifting power 60Kg	**18.24 лв.**	21.89 лв.
	0521A013	Floor Stand for Theater and Parcans projectors *Black finishing *(max. load 10 Kg)	**16.00 лв.**	19.20 лв.

DTS

The Lighting Company

PROUDLY MADE IN ITALY

* използваните изображения не са в пропорционален мащаб помежду си

** Про Аудио ЕООД си запазва правото да променя посочените цени без предупреждение

*** Възможни са печатни грешки

PROAUDIO®
Перфектно контролираната мощност

Про Аудио ЕООД
гр. Бургас
ул. Гладстон № 83
тел/факс 056 / 845204
web: http://www.proaudio.bg
e-mail: contact@proaudio.bg